

Serial DB9 RS232 Extender over Cat 5 - Up to 3300 ft (1000 meters)

Product ID: RS232EXTC1



The RS232EXTC1 Serial over Cat 5 Extender allows you to increase the distance of your RS232 Serial connection by up to 1000 meters (3300 feet), giving you the ability to connect serial peripheral devices up to a kilometer away from your system - an incredible 65x greater than normal RS232 serial cable length restrictions would permit.

The Extender is a cost-effective serial extension solution and completely hardware-based, eliminating the need to install additional software, allowing for a completely plug and play installation. The hardware can be setup in minutes, using existing or new Cat 5 or better Ethernet cabling.

Perfect for use in industrial monitoring and control, POS, security, medical, and traffic flow applications, the RS232 Serial over Cat 5 extender maintains the RS232 standard with support for data transfer rates of up to 230 Kbps.

Backed by a StarTech.com 2-year warranty and free lifetime technical support.

Certifications, Reports and Compatibility

Applications

- Industrial applications include controlling CNC machinery, polling bar code scanner data, administering process control equipment, weigh stations, and other manufacturing applications
- Monitor and control medical equipment, security keypads/card scanners, point of sale equipment and remote sensor data, and various other healthcare related serial communications
- Extend connectivity to Point of Sale card swipe devices, bar code scanners, scales, receipt printers or cash register displays
- Remotely poll data from access keypads, card scanners, camera installations or home security systems



• Remote sensor monitoring for traffic flow management (air traffic control, expressway flow)

Features

- Extend RS232 up to 1000m / 3300ft
- Data transfer rates of up to 230Kbps
- Compatible with all RS232 communications
- Employ existing Cat 5, 5e, 6 or better Ethernet infrastructure to remotely connect serial devices
- Supports full-duplex data communication
- Compact design

Special Notes / Requirements

System and Cable Requirements

• No driver software required for easy Plug-and-Play installation

Hardware			
	Warranty	2 Years	
	Ports	1	
	Cabling	Cat 5 UTP	
Performance			
	Maximum Data Transfer Rate	230 Kbps	
	Max Distance	1 km (0.6 mi)	
Connector(s)			
	Local Unit Connectors	DB-9 (9 pin, D-Sub)	
		RJ-45	
	Remote Unit Connectors	DB-9 (9 pin, D-Sub)	
		RJ-45	
Software			
	OS Compatibility	OS independent	

Cat5 RJ45 cabling required



Power

Power Source 2 AC Adapters Included

Input Voltage 100 - 240 AC

Input Current 55mA

Output Voltage 9V DC

Output Current 0.3A

Center Tip Polarity Positive

Plug Type M

Power Consumption (In 2.

Watts)

Environmental

Operating Temperature 0C to 70C (32F to 158F)

Storage Temperature 0C to 85C (32F to 185F)

Humidity 0% to 95%

Physical Characteristics

Color Silver

Material Steel

Product Length 3.6 in [92 mm]

Product Width 1.3 in [34 mm]

Product Height 0.9 in [22 mm]

Weight of Product 9.6 oz [273 g]

Packaging Information

Package Length 5.6 in [14.2 cm]

Package Width 12.5 in [31.8 cm]

Package Height 2.4 in [60 mm]

Shipping (Package) 23.7 oz [672 g]



Weight

What's in the Box

Included in Package RS232 Extender Local Unit

RS232 Extender Remote Unit

20cm Null Modem cable (DB-9 Male to Male)

Power Adapter

User Manual

^{*}Product appearance and specifications are subject to change without notice.