


# Flat cylinder DZF-12-125-A-P-A

Part number: 161230

FESTO



## Data sheet

| Feature                                      | Value  |
|--|--|
| Stroke                                       | 125 mm   |
| Piston diameter                              | 12 mm<br>Equivalent diameter                                       |
| Max. angle of rotation of the piston rod +/- | 2.5 deg  |
| Type code                                    | DZF  |
| Cushioning                                   | Elastic cushioning rings/pads at both ends                         |
| Mounting position                            | Any  |
| Mode of operation                            | Double-acting  |
| Structural design                            | Piston<br>Piston rod   |
| Position sensing                             | For proximity sensor   |
| Symbol                                       | 00991217   |
| Protection against torsion/guide             | Oval piston  |
| Operating pressure                           | 0.16 MPa ... 1 MPa   |
| Operating pressure                           | 1.6 bar ... 10 bar   |
| Operating medium                             | Compressed air as per ISO 8573-1:2010 [7:4:4]                      |
| Information on operating and pilot media     | Operation with oil lubrication possible (required for further use) |
| Corrosion resistance class (CRC)             | 2 - Moderate corrosion stress                                      |
| Ambient temperature                          | -20 °C ... 80 °C   |
| Max. torque for protection against rotation  | 0.1 Nm   |
| Theoretical force at 6 bar, retracting       | 51 N   |
| Theoretical force at 6 bar, advancing        | 68 N   |
| Moving mass at 0 mm stroke                   | 12 g   |
| Additional weight per 10 mm stroke           | 9 g  |
| Basic weight with 0 mm stroke                | 96 g   |
| Additional moving mass per 10 mm stroke      | 2 g  |
| Type of mounting                             | Optionally:<br>With internal thread<br>With accessories            |
| Pneumatic connection                         | M5   |
| Cover material                               | Wrought aluminum alloy   |
| Seals material                               | NBR<br>TPE-U(PU)   |
| Housing material                             | Aluminum<br>Smooth anodized  |
| Piston rod material                          | High-alloy stainless steel   |