



SAFETY DATA SHEET

1. Identification

Product identifier Battery Terminal Protector - 7.5 oz

Other means of identification

Product Code No. 03175 (Item# 1003433)

Recommended use Battery terminal protector

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufactured or sold by:

Company name CRC Industries, Inc.

Address 885 Louis Dr.
Warminster, PA 18974 US

Telephone

General Information 215-674-4300

Technical Assistance 800-521-3168

Customer Service 800-272-4620

24-Hour Emergency (CHEMTREC) 800-424-9300 (US)

Website www.crcindustries.com

2. Hazard(s) identification

Physical hazards	Flammable aerosols	Category 1
	Gases under pressure	Liquefied gas
Health hazards	Skin corrosion/irritation	Category 2
	Carcinogenicity	Category 2
	Reproductive toxicity	Category 2
	Specific target organ toxicity, single exposure	Category 3 narcotic effects
	Specific target organ toxicity, repeated exposure	Category 2 (central nervous system, hearing organs, kidney, liver)
Environmental hazards	Aspiration hazard	Category 1
	Hazardous to the aquatic environment, acute hazard	Category 2
	Hazardous to the aquatic environment, long-term hazard	Category 2
OSHA defined hazards	Not classified.	

Label elements



Signal word

Danger

Hazard statement

Extremely flammable aerosol. Contains gas under pressure; may explode if heated. May be fatal if swallowed and enters airways. Causes skin irritation. May cause drowsiness or dizziness. Suspected of causing cancer. Suspected of damaging fertility or the unborn child. May cause damage to organs (central nervous system, hearing organs, kidney, liver) through prolonged or repeated exposure.

Precautionary statement

Prevention

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not breathe the mist or vapor. Do not apply while equipment is energized. Extinguish all flames, pilot lights, and heaters. Vapors will accumulate readily and may ignite. Use only outdoors or in a well-ventilated area. Maintain ventilation during use and until all vapors are gone. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection.

Response

If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. If on skin: Wash with plenty of water. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. If exposed or concerned: Get medical advice/attention.

Storage

Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Exposure to high temperature may cause can to burst.

Disposal

Dispose of contents/container in accordance with local/regional/national regulations.

Hazard(s) not otherwise classified (HNOC)

Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapor. May cause flash fire or explosion.

Supplemental information

None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
naphtha (petroleum), hydrotreated light		64742-49-0	30 - 40
liquefied petroleum gas		68476-86-8	20 - 30
petrolatum		8009-03-8	10 - 20
heptane, branched, cyclic and linear		426260-76-6	5 - 10
n-heptane		142-82-5	5 - 10
2-methylpentane		107-83-5	3 - 5
xylene		1330-20-7	3 - 5
ethylbenzene		100-41-4	1 - 3
paraffin oils (petroleum), catalytic dewaxed heavy		64742-70-7	1 - 3
solvent naphtha (petroleum), light aliph.		64742-89-8	1 - 3
distillates (petroleum), hydrotreated heavy paraffinic		64742-54-7	0.1 - 1
paraffin oils (petroleum), catalytic dewaxed light		64742-71-8	0.1 - 1
n-hexane		110-54-3	< 0.3

Constituents

Chemical name	Common name and synonyms	CAS number	%
propane		74-98-6	10 - 20
n-butane		106-97-8	10 - 20

Specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison center or doctor/physician if you feel unwell.

Skin contact

Remove contaminated clothing. Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.

Eye contact

Rinse with water. Get medical attention if irritation develops and persists.

Ingestion	Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.
Most important symptoms/effects, acute and delayed	Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness and dizziness. Headache. Nausea, vomiting. Skin irritation. May cause redness and pain. Prolonged exposure may cause chronic effects.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
General information	IF exposed or concerned: Get medical advice/attention. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.

5. Fire-fighting measures

Suitable extinguishing media	Water fog. Foam. Carbon dioxide (CO2). Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Contents under pressure. Pressurized container may rupture when exposed to heat or flame. This product is a poor conductor of electricity and can become electrostatically charged. If sufficient charge is accumulated, ignition of flammable mixtures can occur. Static electricity accumulation may be significantly increased by the presence of small quantities of water or other contaminants. Material will float and may ignite on surface of water. During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
Fire-fighting equipment/instructions	In case of fire: Stop leak if safe to do so. Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. Use standard firefighting procedures and consider the hazards of other involved materials. In the event of fire and/or explosion do not breathe fumes.
General fire hazards	Extremely flammable aerosol. Contents under pressure. Pressurized container may rupture when exposed to heat or flame.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Remove all possible sources of ignition in the surrounding area. Keep out of low areas. Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks). Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Emergency personnel need self-contained breathing equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Use appropriate containment to avoid environmental contamination. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Prevent product from entering drains. Stop the flow of material, if this is without risk. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground. Use appropriate containment to avoid environmental contamination.

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Minimize fire risks from flammable and combustible materials (including combustible dust and static accumulating liquids) or dangerous reactions with incompatible materials. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Use caution around energized equipment. The metal container will conduct electricity if it contacts a live source. This may result in injury to the user from electrical shock and/or flash fire. Do not breathe mist/vapors. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices. For product usage instructions, see the product label.

Conditions for safe storage, including any incompatibilities

Level 3 Aerosol.

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50 °C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Avoid spark promoters. These alone may be insufficient to remove static electricity. Store in tightly closed container. Store in a well-ventilated place. Stored containers should be periodically checked for general condition and leakage. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

U.S. - OSHA

Components

Type

Value

distillates (petroleum),
hydrotreated heavy
paraffinic (CAS 64742-54-7)

TWA

5 mg/m3

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components

Type

Value

Form

distillates (petroleum),
hydrotreated heavy
paraffinic (CAS 64742-54-7)

PEL

5 mg/m3

Mist.

ethylbenzene (CAS
100-41-4)

PEL

435 mg/m3

100 ppm

naphtha (petroleum),
hydrotreated light (CAS
64742-49-0)

PEL

400 mg/m3

100 ppm

n-heptane (CAS 142-82-5)

PEL

2000 mg/m3

500 ppm

n-hexane (CAS 110-54-3)

PEL

1800 mg/m3

500 ppm

paraffin oils (petroleum),
catalytic dewaxed heavy
(CAS 64742-70-7)

PEL

5 mg/m3

Mist.

paraffin oils (petroleum),
catalytic dewaxed light
(CAS 64742-71-8)

PEL

5 mg/m3

Mist.

petrolatum (CAS
8009-03-8)

PEL

5 mg/m3

Mist.

solvent naphtha
(petroleum), light aliph.
(CAS 64742-89-8)

PEL

400 mg/m3

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
xylene (CAS 1330-20-7)	PEL	100 ppm	
		435 mg/m3	

Constituents	Type	Value	
propane (CAS 74-98-6)	PEL	1800 mg/m3	
		1000 ppm	

ACGIH Components	Type	Value	Form
distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)	TWA	5 mg/m3	Inhalable fraction

US. ACGIH Threshold Limit Values

Components	Type	Value	Form
2-methylpentane (CAS 107-83-5)	STEL	1000 ppm	
	TWA	500 ppm	
distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)	TWA	5 mg/m3	Inhalable fraction.
	TWA	20 ppm	
n-heptane (CAS 142-82-5)	STEL	500 ppm	
	TWA	400 ppm	
n-hexane (CAS 110-54-3)	TWA	50 ppm	
	TWA	5 mg/m3	Inhalable fraction.
paraffin oils (petroleum), catalytic dewaxed heavy (CAS 64742-70-7)	TWA	5 mg/m3	Inhalable fraction.
	TWA	5 mg/m3	Inhalable fraction.
petrolatum (CAS 8009-03-8)	TWA	5 mg/m3	Inhalable fraction.
xylene (CAS 1330-20-7)	STEL	150 ppm	
	TWA	100 ppm	

Constituents	Type	Value	
n-butane (CAS 106-97-8)	STEL	1000 ppm	

U.S. - NIOSH

Components	Type	Value	Form
distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)	STEL	10 mg/m3	Mist
	TWA	5 mg/m3	Mist

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value	Form
2-methylpentane (CAS 107-83-5)	Ceiling	1800 mg/m3	
		510 ppm	
	TWA	350 mg/m3	
		100 ppm	

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value	Form
distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.
ethylbenzene (CAS 100-41-4)	STEL	545 mg/m3	
		125 ppm	
	TWA	435 mg/m3 100 ppm	
naphtha (petroleum), hydrotreated light (CAS 64742-49-0)	TWA	400 mg/m3	
		100 ppm	
n-heptane (CAS 142-82-5)	Ceiling	1800 mg/m3	
		440 ppm	
n-hexane (CAS 110-54-3)	TWA	350 mg/m3	
		85 ppm	
	TWA	180 mg/m3	
paraffin oils (petroleum), catalytic dewaxed heavy (CAS 64742-70-7)	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.
paraffin oils (petroleum), catalytic dewaxed light (CAS 64742-71-8)	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.
petrolatum (CAS 8009-03-8)	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.
solvent naphtha (petroleum), light aliph. (CAS 64742-89-8)	TWA	400 mg/m3	
		100 ppm	
xylene (CAS 1330-20-7)	STEL	655 mg/m3	
		150 ppm	
	TWA	435 mg/m3 100 ppm	

Constituents

Components	Type	Value
n-butane (CAS 106-97-8)	TWA	1900 mg/m3 800 ppm
propane (CAS 74-98-6)	TWA	1800 mg/m3 1000 ppm

US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants

Components	Type	Value	Form
2-methylpentane (CAS 107-83-5)	PEL	1800 mg/m3	
		500 ppm	
	STEL	3600 mg/m3 1000 ppm	

US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants

Components	Type	Value	Form
distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)	PEL	5 mg/m3	Mist.
ethylbenzene (CAS 100-41-4)	PEL	22 mg/m3	
		5 ppm	
	STEL	130 mg/m3	
		30 ppm	
naphtha (petroleum), hydrotreated light (CAS 64742-49-0)	PEL	1350 mg/m3	
		300 ppm	
	STEL	1800 mg/m3	
		400 ppm	
n-heptane (CAS 142-82-5)	PEL	1600 mg/m3	
		400 ppm	
	STEL	2000 mg/m3	
		500 ppm	
n-hexane (CAS 110-54-3)	PEL	180 mg/m3	
		50 ppm	
paraffin oils (petroleum), catalytic dewaxed heavy (CAS 64742-70-7)	PEL	5 mg/m3	Mist.
paraffin oils (petroleum), catalytic dewaxed light (CAS 64742-71-8)	PEL	5 mg/m3	Mist.
petrolatum (CAS 8009-03-8)	PEL	5 mg/m3	Mist.
solvent naphtha (petroleum), light aliph. (CAS 64742-89-8)	PEL	1350 mg/m3	
		300 ppm	
	STEL	1800 mg/m3	
		400 ppm	
xylene (CAS 1330-20-7)	Ceiling	300 ppm	
	PEL	435 mg/m3	
		100 ppm	
	STEL	655 mg/m3	
		150 ppm	
Constituents	Type	Value	
n-butane (CAS 106-97-8)	PEL	1900 mg/m3	
		800 ppm	
propane (CAS 74-98-6)	PEL	1800 mg/m3	
		1000 ppm	

Biological limit values

ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling Time
ethylbenzene (CAS 100-41-4)	0.15 g/g	Sum of mandelic acid and phenylglyoxylic acid	Creatinine in urine	*
n-hexane (CAS 110-54-3)	0.5 mg/l	2,5-Hexanedione, without hydrolysis	Urine	*
xylene (CAS 1330-20-7)	1.5 g/g	Methylhippuric acids	Creatinine in urine	*

* - For sampling details, please see the source document.

Exposure guidelines

US - California OELs: Skin designation

n-hexane (CAS 110-54-3)

Can be absorbed through the skin.

US ACGIH Threshold Limit Values: Skin designation

n-hexane (CAS 110-54-3)

Danger of cutaneous absorption

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection

Wear protective gloves such as: Nitrile. Polyvinyl chloride (PVC). Viton rubber (fluor rubber).

Other

Wear appropriate chemical resistant clothing.

Respiratory protection

If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a NIOSH-approved cartridge respirator with an organic vapor cartridge. Use a self-contained breathing apparatus in confined spaces and for emergencies. Air monitoring is needed to determine actual employee exposure levels.

Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Observe any medical surveillance requirements. When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state

Liquid.

Form

Aerosol.

Color

Dark red.

Odor

Petroleum.

Odor threshold

Not available.

pH

Not available.

Melting point/freezing point

-132 °F (-91.1 °C) estimated

Initial boiling point and boiling range

123 °F (50.6 °C) estimated

Flash point

< 0 °F (< -17.8 °C)

Evaporation rate

Fast.

Flammability (solid, gas)

Not available.

Upper/lower flammability or explosive limits

Flammability limit - lower (%)

0.6 % estimated

Flammability limit - upper (%)	7.3 % estimated
Vapor pressure	1451.9 hPa estimated
Vapor density	Not available.
Relative density	0.73
Solubility(ies)	
Solubility (water)	Negligible.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	433 °F (222.8 °C) estimated
Decomposition temperature	Not available.
Viscosity	Not available.
Percent volatile	76.8 % estimated
Other information	
VOC-State Aerosol Coatings (MIR)	1.253

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Heat, flames and sparks. Contact with incompatible materials.
Incompatible materials	Strong acids. Strong oxidizing agents. Halogens.
Hazardous decomposition products	Carbon oxides. Sulfur oxides. Mercaptans. Sulfides. Sodium oxides. Nitrogen oxides (NOx). Formaldehyde.

11. Toxicological information

Information on likely routes of exposure

Inhalation	May cause drowsiness and dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be harmful.
Skin contact	Causes skin irritation.
Eye contact	Direct contact with eyes may cause temporary irritation.
Ingestion	Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.

Symptoms related to the physical, chemical and toxicological characteristics Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness and dizziness. Headache. Nausea, vomiting. Skin irritation. May cause redness and pain.

Information on toxicological effects

Acute toxicity May be fatal if swallowed and enters airways.

Components	Species	Test Results
heptane, branched, cyclic and linear (CAS 426260-76-6)		
Acute		
Dermal		
LD50	Rabbit	> 2000 mg/kg
Inhalation		
LC50	Rat	> 60 mg/l, 4 hours
Oral		
LD50	Rat	> 5000 mg/kg
naphtha (petroleum), hydrotreated light (CAS 64742-49-0)		
Acute		
Dermal		
LD50	Rat	> 2000 mg/kg

Components	Species	Test Results
Inhalation		
<i>Vapor</i>		
LC50	Rat	> 5.2 mg/l, 4 hours
Oral		
LD50	Rat	> 5000 mg/kg
n-heptane (CAS 142-82-5)		
Acute		
Dermal		
LD50	Rabbit	> 2000 mg/kg
Inhalation		
<i>Vapor</i>		
LC50	Rat	> 73.5 mg/l, 4 hours
Oral		
LD50	Rat	> 5000 mg/kg
n-hexane (CAS 110-54-3)		
Acute		
Dermal		
LD50	Rabbit	> 1300 mg/kg
Oral		
LD50	Rat	15840 mg/kg
paraffin oils (petroleum), catalytic dewaxed heavy (CAS 64742-70-7)		
Acute		
Dermal		
LD50	Rabbit	> 2000 mg/kg
Oral		
LD50	Rat	> 5000 mg/kg
Constituents	Species	Test Results
n-butane (CAS 106-97-8)		
Acute		
Inhalation		
LC50	Rat	658 mg/l, 4 Hours
Skin corrosion/irritation	Causes skin irritation.	
Serious eye damage/eye irritation	Direct contact with eyes may cause temporary irritation.	
Respiratory or skin sensitization		
Respiratory sensitization	Not a respiratory sensitizer.	
Skin sensitization	This product is not expected to cause skin sensitization.	
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.	
Carcinogenicity	Suspected of causing cancer.	
IARC Monographs. Overall Evaluation of Carcinogenicity		
distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)	3 Not classifiable as to carcinogenicity to humans.	
ethylbenzene (CAS 100-41-4)	2B Possibly carcinogenic to humans.	
paraffin oils (petroleum), catalytic dewaxed light (CAS 64742-71-8)	3 Not classifiable as to carcinogenicity to humans.	
xylene (CAS 1330-20-7)	3 Not classifiable as to carcinogenicity to humans.	
OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)		
Not listed.		
US. National Toxicology Program (NTP) Report on Carcinogens		
Not listed.		
Reproductive toxicity	Suspected of damaging fertility or the unborn child.	

Specific target organ toxicity - single exposure	May cause drowsiness and dizziness.
Specific target organ toxicity - repeated exposure	May cause damage to organs (central nervous system, hearing organs, kidney, liver) through prolonged or repeated exposure.
Aspiration hazard	May be fatal if swallowed and enters airways.
Chronic effects	May cause damage to organs through prolonged or repeated exposure. Prolonged inhalation may be harmful.

12. Ecological information

Ecotoxicity Toxic to aquatic life with long lasting effects.

Components	Species	Test Results
n-heptane (CAS 142-82-5)		
Aquatic		
<i>Acute</i>		
Crustacea	EC50	Water flea (Daphnia magna) > 10 mg/l, 24 hours 1.5 mg/l, 48 hours
Fish	LC50	Freshwater fish 375 mg/l, 96 hours Goldfish (Carassius auratus) 4 mg/l, 24 hours
n-hexane (CAS 110-54-3)		
Aquatic		
<i>Acute</i>		
Fish	LC50	Fathead minnow (Pimephales promelas) 2500 µg/l, 96 hours

Persistence and degradability No data is available on the degradability of any ingredients in the mixture.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

2-methylpentane	3.21
ethylbenzene	3.15
n-heptane	4.66
n-hexane	3.9

Bioconcentration factor (BCF)

ethylbenzene	1
naphtha (petroleum), hydrotreated light	10 - 2500
n-hexane	501.187
xylene	23.99

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions If discarded, this product is considered a RCRA ignitable waste, D001. Empty container can be recycled. Contents under pressure. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose in accordance with all applicable regulations.

Hazardous waste code D001: Waste Flammable material with a flash point <140 F

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT

UN number	UN1950
UN proper shipping name	Aerosols, flammable, Limited Quantity
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
Packing group	-

Environmental hazards



Marine pollutant	Yes, but exempt from the regulations.
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Special provisions	N82
Packaging exceptions	306
Packaging non bulk	None
Packaging bulk	None

IATA

UN number	UN1950
UN proper shipping name	Aerosols, flammable, Limited Quantity
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Packing group	-
ERG Code	10L
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Other information	
Passenger and cargo aircraft	Allowed with restrictions.
Cargo aircraft only	Allowed with restrictions.

IMDG

UN number	UN1950
UN proper shipping name	AEROSOLS, Limited Quantity
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Packing group	-
Environmental hazards	
Marine pollutant	Yes, but exempt from the regulations.
EmS	F-D, S-U
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

DOT; IMDG**IATA****15. Regulatory information**

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

CERCLA Hazardous Substance List (40 CFR 302.4)

ethylbenzene (CAS 100-41-4)

xylene (CAS 1330-20-7)

CERCLA Hazardous Substances: Reportable quantity

ethylbenzene (CAS 100-41-4)

1000 LBS

xylene (CAS 1330-20-7)

100 LBS

Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.

Other federal regulations**Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**

ethylbenzene (CAS 100-41-4)

n-hexane (CAS 110-54-3)

xylene (CAS 1330-20-7)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

n-butane (CAS 106-97-8)

propane (CAS 74-98-6)

Safe Drinking Water Act (SDWA) Contains component(s) regulated under the Safe Drinking Water Act.**Food and Drug Administration (FDA)** Not regulated.**Superfund Amendments and Reauthorization Act of 1986 (SARA)**

Classified hazard categories	Flammable (gases, aerosols, liquids, or solids)
	Gas under pressure
	Skin corrosion or irritation
	Carcinogenicity
	Reproductive toxicity
	Specific target organ toxicity (single or repeated exposure)
	Aspiration hazard
	Hazard not otherwise classified (HNOC)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical Yes**SARA 313 (TRI reporting)**

Chemical name	CAS number	% by wt.
ethylbenzene	100-41-4	1 - 3
xylene	1330-20-7	3 - 5

US state regulations**US. New Jersey Worker and Community Right-to-Know Act**

2-methylpentane (CAS 107-83-5)

ethylbenzene (CAS 100-41-4)

naphtha (petroleum), hydrotreated light (CAS 64742-49-0)

n-butane (CAS 106-97-8)

n-heptane (CAS 142-82-5)

n-hexane (CAS 110-54-3)

propane (CAS 74-98-6)

solvent naphtha (petroleum), light aliph. (CAS 64742-89-8)

xylene (CAS 1330-20-7)

US. Massachusetts RTK - Substance List

2-methylpentane (CAS 107-83-5)

distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)

ethylbenzene (CAS 100-41-4)

naphtha (petroleum), hydrotreated light (CAS 64742-49-0)

n-butane (CAS 106-97-8)

n-heptane (CAS 142-82-5)

n-hexane (CAS 110-54-3)

paraffin oils (petroleum), catalytic dewaxed heavy (CAS 64742-70-7)
paraffin oils (petroleum), catalytic dewaxed light (CAS 64742-71-8)
petrolatum (CAS 8009-03-8)
propane (CAS 74-98-6)
solvent naphtha (petroleum), light aliph. (CAS 64742-89-8)
xylene (CAS 1330-20-7)

US. Pennsylvania Worker and Community Right-to-Know Law

2-methylpentane (CAS 107-83-5)
distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)
ethylbenzene (CAS 100-41-4)
naphtha (petroleum), hydrotreated light (CAS 64742-49-0)
n-butane (CAS 106-97-8)
n-heptane (CAS 142-82-5)
n-hexane (CAS 110-54-3)
paraffin oils (petroleum), catalytic dewaxed heavy (CAS 64742-70-7)
paraffin oils (petroleum), catalytic dewaxed light (CAS 64742-71-8)
petrolatum (CAS 8009-03-8)
propane (CAS 74-98-6)
solvent naphtha (petroleum), light aliph. (CAS 64742-89-8)
xylene (CAS 1330-20-7)

US. Rhode Island RTK

distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)
ethylbenzene (CAS 100-41-4)
naphtha (petroleum), hydrotreated light (CAS 64742-49-0)
n-butane (CAS 106-97-8)
n-heptane (CAS 142-82-5)
n-hexane (CAS 110-54-3)
paraffin oils (petroleum), catalytic dewaxed heavy (CAS 64742-70-7)
paraffin oils (petroleum), catalytic dewaxed light (CAS 64742-71-8)
petrolatum (CAS 8009-03-8)
propane (CAS 74-98-6)
solvent naphtha (petroleum), light aliph. (CAS 64742-89-8)
xylene (CAS 1330-20-7)

California Proposition 65



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

California Proposition 65 - CRT: Listed date/Carcinogenic substance

benzene (CAS 71-43-2)	Listed: February 27, 1987
cumene (CAS 98-82-8)	Listed: April 6, 2010
ethylbenzene (CAS 100-41-4)	Listed: June 11, 2004
naphthalene (CAS 91-20-3)	Listed: April 19, 2002

California Proposition 65 - CRT: Listed date/Developmental toxin

benzene (CAS 71-43-2)	Listed: December 26, 1997
mercury (CAS 7439-97-6)	Listed: July 1, 1990
toluene (CAS 108-88-3)	Listed: January 1, 1991

California Proposition 65 - CRT: Listed date/Male reproductive toxin

benzene (CAS 71-43-2)	Listed: December 26, 1997
n-hexane (CAS 110-54-3)	Listed: December 15, 2017

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)
ethylbenzene (CAS 100-41-4)
naphtha (petroleum), hydrotreated light (CAS 64742-49-0)
n-butane (CAS 106-97-8)
n-heptane (CAS 142-82-5)
n-hexane (CAS 110-54-3)
paraffin oils (petroleum), catalytic dewaxed heavy (CAS 64742-70-7)
paraffin oils (petroleum), catalytic dewaxed light (CAS 64742-71-8)
petrolatum (CAS 8009-03-8)
solvent naphtha (petroleum), light aliph. (CAS 64742-89-8)
xylene (CAS 1330-20-7)

Volatile organic compounds (VOC) regulations

EPA

Aerosol coatings (40 CFR 59, Subpt. E) Not regulated

State

Aerosol coatings This product is regulated as an Electrical Coating. This product is compliant for sale in all 50 states.

Maximum incremental reactivity (MIR) 1.253

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Industrial Chemicals (AICIS)	No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 06-30-2021

Prepared by Danica Fulmer

Version # 01

Further information CRC # 597P-Q/1002627-1002629

Disclaimer The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC's knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety professional, or CRC Industries, Inc..

Revision information Product and Company Identification: Product Codes
Physical & Chemical Properties: Multiple Properties
GHS: Qualifiers