



V.O.C. COMPLIANT LOW-ODOR HIGH-PERFORMANCE MASTIC REMOVER



Part # 40320

PHYSICAL DATA

Chemical Description.....Emulsified Hydrocarbon
 Color.....Clear to Amber
 Odor.....Mild/Low
 Flashpoint.....>170° F PMCC
 Boiling Point.....415°-420° F
 pH.....neutral
 Evaporation Rate.....Slower than ether
 Shipping Weight.....5 gallon pail.....38 pounds
 55 gallon drum.....435 pounds
 DOT Hazard Class.....Not Regulated
 DOT Shipping Name.....Cleaning Compound NOS
 HMIS Rating.....1-2-0-B
 Coverage.....100 Sq. Ft. per Gallon

CAUTIONS

KEEP OUT OF REACH OF CHILDREN! Use product only as directed.
 Combustible Mixture. Contains Petroleum distillates and Glycol Ethers. Keep away from heat and open flames.
 Avoid contact with eyes and skin. Use only in a well-ventilated areas. Avoid breathing of vapor or mist, especially for those with asthma or allergies. DO NOT USE THIS PRODUCT BEFORE READING THE MATERIAL SAFETY DATA SHEET. Do not transfer to unmarked containers.

PRODUCT DESCRIPTION

Amerisafe Low Odor High Performance Mastic Remover is a low odor, economically priced mastic remover for removing black mastic, cutback and spray adhesives on asbestos abatement jobs. This product does not contain asbestos.

DIRECTIONS FOR USE

Before beginning work, protect all walls, flooring, carpeting, cracks, or wood from liquid materials. This will ensure easier clean-up and eliminate potential problems.

Following removal of floor tile, apply product evenly to the adhesive using a mop, squeegee or sprayer. Allow the remover to soak and penetrate into the adhesive for 15-20 minutes.

Using scrapers, remove the softened adhesive from the floor surface and reapply product to the remaining adhesive residue.

Using brooms or floor scrubbers, agitate the resulting mixture and remove all liquids using absorbents.

Once the mastic and remover are removed, wash the floor of all residues using a soap and water solution. Allow floor to dry completely before installing new flooring.

Manufactured for:
 AMERISAFE INC.
 3390 Enterprise Court
 Aurora, IL 60504
 (630) 862-2600



V.O.C.-Compliant - This floor or wall covering adhesive remover contains less than 5% VOC content by weight, per the requirements set forth by the California Air Resource Board (CARB) and the Ozone Transport Commission (OTC), effective 01-01-2010.