

## 1. Identification

**Product number** 18-0635D  
**Product identifier** **Auralex Foamtak Adhesive**  
**Company information**  
  
**Company phone** General Assistance 1-636-334-9100  
 1-866-836-8855  
**Emergency telephone US** 1-952-852-4646  
**Emergency telephone outside US** 01  
**Version #** Adhesive  
**Recommended use** None known.  
**Recommended restrictions**

## 2. Hazard(s) identification

**Physical hazards** Flammable aerosols  
**Health hazards** Serious eye damage/eye irritation Category 1  
 Specific target organ toxicity, single exposure Category 2A  
 Aspiration hazard Category 3 narcotic effects  
 Not classified. Category 1  
**OSHA defined hazards**

### Label elements



**Signal word** Danger  
**Hazard statement** Extremely flammable aerosol. May be fatal if swallowed and enters airways. Causes serious eye irritation. May cause drowsiness or dizziness.  
**Precautionary statement**  
**Prevention** Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid breathing gas. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear eye protection/face protection.  
**Response** If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a poison center/doctor if you feel unwell. If eye irritation persists: Get medical advice/attention.  
**Storage** Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.  
**Disposal** Dispose of contents/container in accordance with local/regional/national/international regulations.  
**Environmental hazards** Hazardous to the aquatic environment, acute hazard Category 2  
 Hazardous to the aquatic environment, long-term hazard Category 2  
**Hazard(s) not otherwise classified (HNOC)** None known.  
**Supplemental information** None.

### 3. Composition/information on ingredients

#### Mixtures

Chemical name	Common name and synonyms	CAS number	%
Acetone		67-64-1	20 - 40
Butane		106-97-8	10 - 20
Propane		74-98-6	10 - 20
Dimethyl Ether		115-10-6	2.5 - 10
Methyl Acetate		79-20-9	2.5 - 10
Naphtha, (Petroleum), Hydrotreated Light		64742-49-0	2.5 - 10
n-Heptane		142-82-5	2.5 - 10
Parachlorobenzotrifluoride (PCBTF)		98-56-6	1 - 2.5
Other components below reportable levels			20 - 40

\*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

### 4. First-aid measures

<b>Inhalation</b>	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
<b>Skin contact</b>	Wash off with soap and water. Get medical attention if irritation develops and persists.
<b>Eye contact</b>	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
<b>Ingestion</b>	Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.
<b>Most important symptoms/effects, acute and delayed</b>	Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.
<b>Indication of immediate medical attention and special treatment needed</b>	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
<b>General information</b>	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

### 5. Fire-fighting measures

<b>Suitable extinguishing media</b>	Alcohol resistant foam. Powder. Carbon dioxide (CO <sub>2</sub> ).
<b>Unsuitable extinguishing media</b>	Do not use water jet as an extinguisher, as this will spread the fire.
<b>Specific hazards arising from the chemical</b>	Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.
<b>Special protective equipment and precautions for firefighters</b>	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
<b>Fire fighting equipment/instructions</b>	Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.
<b>Specific methods</b>	Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. Use water spray to cool unopened containers. In the event of fire and/or explosion do not breathe fumes.
<b>General fire hazards</b>	Extremely flammable aerosol.

### 6. Accidental release measures

<b>Personal precautions, protective equipment and emergency procedures</b>	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing gas. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
--	--

## Methods and materials for containment and cleaning up

Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Prevent entry into waterways, sewer, basements or confined areas. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.

## Environmental precautions

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

## 7. Handling and storage

### Precautions for safe handling

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Avoid breathing gas. Avoid contact with eyes. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices.

### Conditions for safe storage, including any incompatibilities

Level 2 Aerosol.

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store away from incompatible materials (see Section 10 of the SDS).

## 8. Exposure controls/personal protection

### Occupational exposure limits

#### US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value
Acetone (CAS 67-64-1)	PEL	2400 mg/m3 1000 ppm
Methyl Acetate (CAS 79-20-9)	PEL	610 mg/m3 200 ppm
n-Heptane (CAS 142-82-5)	PEL	2000 mg/m3 500 ppm
Propane (CAS 74-98-6)	PEL	1800 mg/m3 1000 ppm

#### US. ACGIH Threshold Limit Values

Components	Type	Value
Acetone (CAS 67-64-1)	STEL	500 ppm
	TWA	250 ppm
Butane (CAS 106-97-8)	STEL	1000 ppm
Methyl Acetate (CAS 79-20-9)	STEL	250 ppm
	TWA	200 ppm
n-Heptane (CAS 142-82-5)	STEL	500 ppm
	TWA	400 ppm

#### US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value
Acetone (CAS 67-64-1)	TWA	590 mg/m3 250 ppm
Butane (CAS 106-97-8)	TWA	1900 mg/m3 800 ppm
Methyl Acetate (CAS 79-20-9)	STEL	760 mg/m3

**US. NIOSH: Pocket Guide to Chemical Hazards**

Components	Type	Value
n-Heptane (CAS 142-82-5)	TWA	250 ppm
		610 mg/m3
	Ceiling	200 ppm
		1800 mg/m3
Propane (CAS 74-98-6)	TWA	440 ppm
		350 mg/m3
	TWA	85 ppm
		1800 mg/m3
		1000 ppm

**US. Workplace Environmental Exposure Level (WEEL) Guides**

Components	Type	Value
Dimethyl Ether (CAS 115-10-6)	TWA	1880 mg/m3
		1000 ppm

**Biological limit values****ACGIH Biological Exposure Indices**

Components	Value	Determinant	Specimen	Sampling Time
Acetone (CAS 67-64-1)	25 mg/l	Acetone	Urine	*

\* - For sampling details, please see the source document.

**Appropriate engineering controls**

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.

**Individual protection measures, such as personal protective equipment**

**Eye/face protection** Wear safety glasses with side shields (or goggles).

**Skin protection****Hand protection**

Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove supplier.

**Other**

Wear suitable protective clothing.

**Respiratory protection**

If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator.

**Thermal hazards**

Wear appropriate thermal protective clothing, when necessary.

**General hygiene considerations**

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

**9. Physical and chemical properties****Appearance****Physical state**

Gas.

**Form**

Aerosol.

**Color**

Not available.

**Odor**

Not available.

**Odor threshold**

Not available.

**pH**

Not available.

**Melting point/freezing point**

Not available.

**Initial boiling point and boiling range**

151.48 °F (66.38 °C) estimated

**Flash point**

-156.0 °F (-104.4 °C) estimated

**Evaporation rate**

Not available.

**Flammability (solid, gas)**

Not available.

## Upper/lower flammability or explosive limits

<b>Flammability limit - lower (%)</b>	2.2 % estimated
<b>Flammability limit - upper (%)</b>	11.4 % estimated
<b>Explosive limit - lower (%)</b>	Not available.
<b>Explosive limit - upper (%)</b>	Not available.

**Vapor pressure** 50 - 70 psig @20c estimated  
105 - 125 psig @54C estimated

**Vapor density** Not available.

**Relative density** Not available.

## Solubility(ies)

**Solubility (water)** Not available.

**Partition coefficient (n-octanol/water)** Not available.

**Auto-ignition temperature** 762.01 °F (405.56 °C) estimated

**Decomposition temperature** Not available.

**Viscosity** Not available.

## Other information

**Explosive properties** Not explosive.

**Heat of combustion (NFPA 30B)** 26.48 kJ/g estimated

**Oxidizing properties** Not oxidizing.

**Specific gravity** 0.788 estimated

**VOC (Weight %)** 38.6 % estimated

## 10. Stability and reactivity

**Reactivity** The product is stable and non-reactive under normal conditions of use, storage and transport.

**Chemical stability** Material is stable under normal conditions.

**Possibility of hazardous reactions** Hazardous polymerization does not occur.

**Conditions to avoid** Avoid temperatures exceeding the flash point. Contact with incompatible materials.

**Incompatible materials** Strong oxidizing agents. Nitrates. Fluorine. Chlorine.

**Hazardous decomposition products** No hazardous decomposition products are known.

## 11. Toxicological information

### Information on likely routes of exposure

<b>Inhalation</b>	May cause drowsiness and dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be harmful.
<b>Skin contact</b>	No adverse effects due to skin contact are expected.
<b>Eye contact</b>	Causes serious eye irritation.
<b>Ingestion</b>	Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.

**Symptoms related to the physical, chemical and toxicological characteristics** Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.

### Information on toxicological effects

**Acute toxicity** May be fatal if swallowed and enters airways. Narcotic effects.

Components	Species	Test Results
Acetone (CAS 67-64-1)		
<b><u>Acute</u></b>		
<b>Dermal</b>		
LD50	Guinea pig	> 7426 mg/kg, 24 Hours
		> 9.4 ml/kg, 24 Hours
	Rabbit	> 7426 mg/kg, 24 Hours
		> 9.4 ml/kg, 24 Hours
<b>Inhalation</b>		
LC50	Rat	55700 ppm, 3 Hours
		132 mg/l, 3 Hours
		50.1 mg/l
<b>Oral</b>		
LD50	Rat	5800 mg/kg
		2.2 ml/kg
Butane (CAS 106-97-8)		
<b><u>Acute</u></b>		
<b>Inhalation</b>		
LC50	Mouse	1237 mg/l, 120 Minutes
		52 %, 120 Minutes
	Rat	1355 mg/l
Dimethyl Ether (CAS 115-10-6)		
<b><u>Acute</u></b>		
<b>Inhalation</b>		
NOEL	Rat	2 ppm, 6 Hours
Methyl Acetate (CAS 79-20-9)		
<b><u>Acute</u></b>		
<b>Dermal</b>		
LD50	Rat	> 2000 mg/kg, 24 Hours
<b>Inhalation</b>		
LC100	Rabbit	98.4 mg/l, 4 Hours
<b>Oral</b>		
LD50	Rat	6482 mg/kg
Naphtha, (Petroleum), Hydrotreated Light (CAS 64742-49-0)		
<b><u>Acute</u></b>		
<b>Dermal</b>		
LD50	Guinea pig; Rabbit	> 9.4 ml/kg, 24 Hours
	Rabbit	> 1900 mg/kg, 24 Hours
<b>Inhalation</b>		
LC50	Rat	> 5000 mg/m3, 4 Hours
		> 4980 mg/m3
		> 4980 mg/m3, 4 Hours
		> 4.96 mg/l, 4 Hours
		13700 ppm, 4 Hours
<b>Oral</b>		
LD50	Rat	4820 mg/kg
n-Heptane (CAS 142-82-5)		
<b><u>Acute</u></b>		
<b>Dermal</b>		
LD50	Rabbit	> 2000 mg/kg, 24 Hours

Components	Species	Test Results
<b>Inhalation</b>		
LC50	Rat	> 29.29 mg/l, 4 Hours
<b>Oral</b>		
LD50	Rat	> 5000 mg/kg
Parachlorobenzotrifluoride (PCBTF) (CAS 98-56-6)		
<b>Acute</b>		
<b>Dermal</b>		
LD50	Rabbit	0.126 ml/kg, 24 Hours
	Rat	0.5 - 1 ml/kg
<b>Inhalation</b>		
LC50	Mouse	200 ppm, 4 Hours
	Rat	220 ppm, 4 Hours
<b>Oral</b>		
LD50	Rat	382 mg/kg
		1.39 ml/kg
Propane (CAS 74-98-6)		
<b>Acute</b>		
<b>Inhalation</b>		
LC50	Mouse	1237 mg/l, 120 Minutes
		52 %, 120 Minutes
	Rat	1355 mg/l
		658 mg/l/4h

\* Estimates for product may be based on additional component data not shown.

<b>Skin corrosion/irritation</b>	Prolonged skin contact may cause temporary irritation.
<b>Serious eye damage/eye irritation</b>	Causes serious eye irritation.
<b>Respiratory or skin sensitization</b>	
<b>Respiratory sensitization</b>	Not a respiratory sensitizer.
<b>Skin sensitization</b>	This product is not expected to cause skin sensitization.
<b>Germ cell mutagenicity</b>	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.
<b>Carcinogenicity</b>	Risk of cancer cannot be excluded with prolonged exposure.
<b>IARC Monographs. Overall Evaluation of Carcinogenicity</b>	
Not listed.	
<b>OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)</b>	
Not regulated.	
<b>US. National Toxicology Program (NTP) Report on Carcinogens</b>	
Not listed.	
<b>Reproductive toxicity</b>	This product is not expected to cause reproductive or developmental effects.
<b>Specific target organ toxicity - single exposure</b>	May cause drowsiness and dizziness.
<b>Specific target organ toxicity - repeated exposure</b>	Not classified.
<b>Aspiration hazard</b>	May be fatal if swallowed and enters airways.
<b>Chronic effects</b>	Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

## 12. Ecological information

**Ecotoxicity** Toxic to aquatic life with long lasting effects.

Components	Species		Test Results
Acetone (CAS 67-64-1)			
<b>Aquatic</b>			
Crustacea	EC50	Water flea (Daphnia magna)	21.6 - 23.9 mg/l, 48 hours
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	4740 - 6330 mg/l, 96 hours
Dimethyl Ether (CAS 115-10-6)			
<b>Aquatic</b>			
Crustacea	EC50	Water flea (Daphnia pulex)	4.3 - 7.8 mg/l, 48 hours
Fish	LC50	Striped bass (Morone saxatilis)	10.302 - 16.743 mg/l, 96 hours
Methyl Acetate (CAS 79-20-9)			
<b>Aquatic</b>			
Algae	IC50	Algae	120.0001 mg/L, 72 Hours
Crustacea	EC50	Daphnia	1026.7 mg/L, 48 Hours
Fish	LC50	Fathead minnow (Pimephales promelas)	295 - 348 mg/l, 96 hours
n-Heptane (CAS 142-82-5)			
<b>Aquatic</b>			
Fish	LC50	Mozambique tilapia (Tilapia mossambica)	375 mg/l, 96 hours

\* Estimates for product may be based on additional component data not shown.

**Persistence and degradability** No data is available on the degradability of this product.

**Bioaccumulative potential**

**Partition coefficient n-octanol / water (log Kow)**

Acetone	-0.24
Butane	2.89
Dimethyl Ether	0.1
Methyl Acetate	0.18
n-Heptane	4.66
Propane	2.36

**Mobility in soil** No data available.

**Other adverse effects** No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

**13. Disposal considerations**

**Disposal instructions** Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.

**Local disposal regulations** Dispose in accordance with all applicable regulations.

**Hazardous waste code** The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

**Waste from residues / unused products** Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

**Contaminated packaging** Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.

**14. Transport information**

**DOT**

<b>UN number</b>	UN1950
<b>UN proper shipping name</b>	Aerosols, flammable, (each not exceeding 1 L capacity)
<b>Transport hazard class(es)</b>	
<b>Class</b>	2.1
<b>Subsidiary risk</b>	-



<b>Label(s)</b>	2.1
<b>Packing group</b>	Not applicable.
<b>Special precautions for user</b>	Read safety instructions, SDS and emergency procedures before handling.
<b>Special provisions</b>	N82
<b>Packaging exceptions</b>	306
<b>Packaging non bulk</b>	None
<b>Packaging bulk</b>	None

This product meets the exception requirements of section 173.306 as a limited quantity and may be shipped as a limited quantity. Until 12/31/2020, the "Consumer Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/20 and may be used now in place of the "Consumer Commodity ORM-D" marking.

#### IATA

<b>UN number</b>	UN1950
<b>UN proper shipping name</b>	Aerosols, flammable
<b>Transport hazard class(es)</b>	
<b>Class</b>	2.1
<b>Subsidiary risk</b>	-
<b>Label(s)</b>	2.1
<b>Packing group</b>	Not applicable.
<b>Environmental hazards</b>	Yes
<b>ERG Code</b>	10L
<b>Special precautions for user</b>	Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.
<b>Other information</b>	
<b>Passenger and cargo aircraft</b>	Allowed with restrictions.
<b>Cargo aircraft only</b>	Allowed with restrictions.
<b>Packaging Exceptions</b>	LTD QTY

#### IMDG

<b>UN number</b>	UN1950
<b>UN proper shipping name</b>	AEROSOLS
<b>Transport hazard class(es)</b>	
<b>Class</b>	2.1
<b>Subsidiary risk</b>	-
<b>Label(s)</b>	None
<b>Packing group</b>	Not applicable.
<b>Environmental hazards</b>	
<b>Marine pollutant</b>	Yes
<b>EmS</b>	F-D, S-U
<b>Special precautions for user</b>	Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.
<b>Packaging Exceptions</b>	LTD QTY

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code** Not applicable.

#### DOT



IATA; IMDG



Marine pollutant



General information

DOT Regulated Marine Pollutant. IMDG Regulated Marine Pollutant.

## 15. Regulatory information

### US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

#### TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Parachlorobenzotrifluoride (PCBTF) (CAS 98-56-6) 1.0 % One-Time Export Notification only.

#### CERCLA Hazardous Substance List (40 CFR 302.4)

Acetone (CAS 67-64-1) Listed.

#### SARA 304 Emergency release notification

Not regulated.

#### OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

### Superfund Amendments and Reauthorization Act of 1986 (SARA)

#### Hazard categories

Immediate Hazard - Yes  
Delayed Hazard - No  
Fire Hazard - Yes  
Pressure Hazard - Yes  
Reactivity Hazard - No

#### SARA 302 Extremely hazardous substance

Not listed.

#### SARA 311/312 Hazardous chemical

No

#### SARA 313 (TRI reporting)

Not regulated.

### Other federal regulations

#### Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

#### Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Butane (CAS 106-97-8)  
Dimethyl Ether (CAS 115-10-6)  
Propane (CAS 74-98-6)

#### Safe Drinking Water Act (SDWA)

Not regulated.

#### Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number

Acetone (CAS 67-64-1)

6532

**Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))**

Acetone (CAS 67-64-1) 35 %WV

**DEA Exempt Chemical Mixtures Code Number**

Acetone (CAS 67-64-1) 6532

**US state regulations****US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)**

Not listed.

**US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))**Acetone (CAS 67-64-1)  
Butane (CAS 106-97-8)  
Naphtha, (Petroleum), Hydrotreated Light (CAS 64742-49-0)**US. Massachusetts RTK - Substance List**Acetone (CAS 67-64-1)  
Butane (CAS 106-97-8)  
Dimethyl Ether (CAS 115-10-6)  
Methyl Acetate (CAS 79-20-9)  
n-Heptane (CAS 142-82-5)  
Propane (CAS 74-98-6)**US. New Jersey Worker and Community Right-to-Know Act**Acetone (CAS 67-64-1)  
Butane (CAS 106-97-8)  
Dimethyl Ether (CAS 115-10-6)  
Methyl Acetate (CAS 79-20-9)  
n-Heptane (CAS 142-82-5)  
Propane (CAS 74-98-6)**US. Pennsylvania Worker and Community Right-to-Know Law**Acetone (CAS 67-64-1)  
Butane (CAS 106-97-8)  
Dimethyl Ether (CAS 115-10-6)  
Methyl Acetate (CAS 79-20-9)  
n-Heptane (CAS 142-82-5)  
Propane (CAS 74-98-6)**US. Rhode Island RTK**Acetone (CAS 67-64-1)  
Butane (CAS 106-97-8)  
Dimethyl Ether (CAS 115-10-6)  
Propane (CAS 74-98-6)**US. California Proposition 65**

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

**US - California Proposition 65 - CRT: Listed date/Carcinogenic substance**Acetaldehyde (CAS 75-07-0) Listed: April 1, 1988  
Benzene (CAS 71-43-2) Listed: February 27, 1987  
Ethyl Benzene (CAS 100-41-4) Listed: June 11, 2004  
Myrcene (CAS 123-35-3) Listed: March 27, 2015  
Naphthalene (CAS 91-20-3) Listed: April 19, 2002**US - California Proposition 65 - CRT: Listed date/Developmental toxin**Benzene (CAS 71-43-2) Listed: December 26, 1997  
Methanol (CAS 67-56-1) Listed: March 16, 2012  
Toluene (CAS 108-88-3) Listed: January 1, 1991**US - California Proposition 65 - CRT: Listed date/Male reproductive toxin**

Benzene (CAS 71-43-2) Listed: December 26, 1997

**International Inventories**

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No

Country(s) or region	Inventory name	On inventory (yes/no)*
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

## 16. Other information, including date of preparation or last revision

**Issue date** 01-14-2019

**Version #** 01

**Disclaimer** The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.