



Engineered
 for the
EXTREME

FEATURES AND BENEFITS

The Uvex SW09 Livewire™ Rx Sealed Eyewear delivers the fit, performance and protection required in extreme environments, protecting workers against intense wind, sun, dirt, dust and debris, as well as high heat and humidity, with a host of features that include:

- A smooth, yet dense foam sub frame designed to minimize pressure against the skin and offer superior comfort for a complete, all-day sealed fit.
- Ratcheting temples that adjust the lens angle by up to 15° for optimal coverage and air circulation.
- A simple temple-to-headband exchange system makes switching between temples or headband quick and easy.
- Meets ANSI Z87.1-2010 and CSA Z94.3 standards.



Black



Red



Blue



RED - Red



BLU - Blue



BLK - Black

Colors: BLK - Black, RED - Red, BLU - Blue

Frame Sizes: 6 BASE - 56.21.127 8 BASE - 59.21.127

Frame Identification: SW09 Livewire™ Rx Sealed Eyewear




Hinge Type: Plastic, 3 position ratchet. Removable temples, includes headband.

Miscellaneous: Sold assembled only. RS not available.

Features: Close fitting, ratcheting temples, foam gasket. Interchangeable temples and headband.



The **Uvex SW09 Livewire™ Rx Safety Frame** is built with the same sealed eyewear performance and fit as the Uvex Livewire, and is offered in three color options, with 6-base and 8-base lens configurations to accommodate almost any safety eyewear prescription. To add the Uvex SW09 Livewire to your Prescription Safety Eyewear Program, simply provide the enclosed sizing card to your current optical supplier. To learn more about implementing a Prescription Safety Eyewear Program or to locate a Provider in your area, call our Customer Care Department at 800-446-1802 or visit www.uvexrx.com.



FRAME	EYE SIZE	"A"	"B"	DIFFERENCE	D.B.L.	"E.D." ANGLE	"E.D."
6 BASE	56	56.15	36	20.15	21	20.45	58.63
8 BASE	59	59.19	36.18	23.01	21	15.76	61.31



Uvex Safety Rx Eyewear
800-446-1802
www.uvexrx.com

URX.518