Material Data Sheet

CHE	MEQ						
Chemteq, Inc.	ı	Material Data Sheet					
600 West 24th St	1	No. 2511885					
Norfolk, Virginia 23517, USA			Revision: 041021-B				
Tel: 757-622-22		Part Number: 2511					
Toll-free: 855-C	HEMTEQ (855-2	243-6837))	Description	n: Amn	nonia DG Filter with ESLI	
info@chemteg.net Product Name: DG Filter-2511-ESLI							
SECTION 1 - MA		ΙCΔΤΙΩΝ					
SECTION 1 - MA		CAS	: #	% by Weight			
Ingredient Activated Carbon:			7440-44			>58%	
			7664-38			<32%	
Phosphoric Acid							
Polyvinyl Chloride:			None			45-50	
Stainless Steel			None			2.0 - 2.5	
Poly ester			None		е	0.5	
Polyacrylic			None		e	0.1-0.2	
SECTION 2 - HAZ	ARDS IDENTIFI	CATION					
LIMI	CDATINGC		NEDA DAT	INICC		CLUD	
НМІ	S RATINGS		NFPA RATINGS			GUID	
HEALTH		1		4-EXTRE		CTREME/SEVERE	
		· ·				HIGH/SERIOUS	
FLAMMABILITY		1				MODERATE	
FLAMIMADILITI		'	1 0			LIGHT	
						MINIMUM	
PHYSICAL HAZA	ARD	0	\ \ \ \			WATER REACTIVE	
		_				OX - OXIDIZER	
PERSONAL PRO		E					
PICTOGRAM			SIGNAL WORD		Н	HAZARD STATEMENT	
<u>(1)</u>			WARNING			H315: Causes skin irritation H320: Causes eye irritation	
PRECAUTIONARY	STATEMENT(S)					
PREVENTION	P261: Avoid br	eathing d	ng dust/fume. P264: Wash thoroughly after handling				
RESPONSE	P305: IF IN EY	ES: Irriga	ate for 15 minutes. P304: IF INHALED: Remove to fresh air				
STORAGE		re in a dry place. P403: Store in a well-ventilated place. P404: Store in a					
OTHER HAZARDS							
		t of this n	roduct is classifie	d ac haz:	ardous	by OSHA	
SECTION 3 - FIF			i oudct is classifie	u as naze	ai uous i	by OSHA.	
NECESSARY FIR							
INHALATION FIRST AID breath		emove affected person to fresh air. Give artificial respiration ONLY if eathing has stopped and give CPR ONLY if there is no breathing and pulse. Obtain medical attention immediately.					
SKIN CONTACT FIRST AID be was		sh skin for 5 minutes with flowing water and soap. Clothing should washed before reuse. Obtain medical assistance if irritation relops.					
EYE CONTACT FIRST AID Imme minu before		inmediately irrigate eyes with flowing water continuously for 15 inutes while holding eyelids open. Contacts should be removed efore or during flushing. Get medical assistance if irritation eyelops.					
			enty of water. Obtain medical attention immediately.				
DESCRIPTION OF MOST IMPORTANT SYMPTOMS							
No Additional In	formation Avail	able.					
RECOMMENDAT	IONS FOR IMME	DIATE ME	EDICAL CARF				
RECOMMENDAL	ISTAS I OIL IMME	DIAIL MI	DIONE ONKE				

No Additional Information Available.

SECTION 4 - FIRE FIGHTING MEASURES

Suitable Extinguishing Media: Water spray, carbon Dioxide, Foam or Dry Chemical.

Unsuitable Extinguishing Media: None known

Specific Hazards: Avoid producing suspensions of dust during handling and avoid exposure of suspensions to sources of ignition. Suspensions of - 40 mesh particles may explode if exposed to strong ignition sources.

Carbon monoxide and carbon dioxide gas may be emitted upon combustion of material Contact with strong oxidizers such as ozone or liquid oxygen may cause rapid combustion.

Protective Equipment and Procedures: In the event of a fire, wear full protective clothing and NIOSH approved self-contained breathing apparatus with full face piece, operated in positive pressure mode.

SECTION 5 - ACCIDENTAL RELEASE MEASURES

Personal Precautions: Handle in accordance with good industrial hygiene and safety practices. These practices include avoiding unnecessary exposure and removal of a material from eyes, skin, and clothing. Environmental Precautions: The impregnate on this product is water soluble. Dike all entrances to sewers

Containment & Clean-up: Clean up spills in a manner that does not disperse dust into the air. Avoid introducing materials into waterway.

SECTION 6 - HANDLING AND STORAGE

Precautions for Safe Handling: Avoid dispersion into air, Keep containers dry and closed. Follow good handling and housekeeping practices to minimize spills, generation of airborne dusts, and accumulation of dusts on exposed surfaces. Use with adequate exhaust ventilation to draw dust away from workers' breathing zones. Prevent or minimize exposures to dusts by using appropriate respirators, gloves and eye protection. Wash exposed skin areas thoroughly with soap and water. Use caution when pouring, using pneumatic transport, swirling, etc. as this material can become electrostatically charged and present a dust explosion hazard.

Conditions for Safe Storage: Avoid spilling material so as to avoid creating a dust suspension. Store at ambient atmospheric conditions. Product should be stored in a closed dry container. Maintain good housekeeping procedures. Store away from strong oxidizers such as ozone, liquid oxygen, chlorine, permanganate, etc.

SECTION 7 - EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING CONTROLS

Provide ventilation if necessary, to minimize exposure. General ventilation is usually acceptable, but local mechanical exhaust ventilation is preferred at sources of air contamination such as open process equipment.

RESPIRATORY PROTECTION

If use conditions generate dust levels above the TLV / PEL, wear a NIOSH-approved particulate respirator or a NIOSH-approved cartridge respirator fitted with dust filters.

SKIN PROTECTION

Wear appropriate dust resistant clothing and gloves.

EYE/FACE PROTECTION

Safety glasses with side shields. If eye contact or dusty conditions are likely, wear dust tight goggles.

Auto Ignition Temperature

SECTION 8 - PHYSICAL/CHEMICAL PROPERTIES

Physical State (Appearance): Cartridge with ESLI filled with activated carbon sorbent Color Molecular Weight NΑ Odor None Odor Threshold None pH Value Vapor Pressure NA Melting Point Vapor Density Solid Freezina Point NA Relative Density MA Initial Boiling Point NΑ Solubility Not Soluble

Flashpoint **Partition Coefficient** NA NΑ **Evaporation Rate**

Decomposition Temperature NA Flammability NA NA Viscosity NA

SECTION 9 - STABILITIY AND REACTIVITY

This material is considered to be non-reactive under normal use conditions.

NA

No data available

CONDITIONS TO AVOID

Contact with strong oxidizers such as ozone, liquid oxygen, chlorine, permanganate, etc. may result in rapid combustion. Avoid contact with strong acids.

SECTION 10 - TOXICOLOGICAL INFIRMATION

INHALATION: Acute. Inhalation of carbon dust is mildly irritating to the lungs and can immediately give rise to an increased mucociliary transport and airway resistance mediated by the vagus. Inhalation LC50 (Rat) > 64.4 mg / l

CHRONIC: There are no known chronic inhalation effects

SKIN CONTACT: No health effects are expected

EYE CONTACT: Eye contact can cause conjunctivitis, epithelial hyperplasia of the cornea, as well as eczematous inflammation of the eyelids

INGESTION: No health effects are expected

Additional Information:

This product, when used under reasonable conditions and in accordance with the directions for use, should not present a health hazard. However, use or processing of the product in a manner not in accordance with the product's directions for use may affect the performance of the product and may present potential

SECTION 11 - ECOLOGICAL INFIRMATION

The material, in its original state, is not harmful to the environment.

SECTION 12 - DISPOSAL CONSIDERATIONS

Dispose of contents/container in accordance with the local/regional/national/international regulations.

SECTION 13 - TRANSPORT INFORMATION

DOT Shipping Description: see shipping papers

SECTION 14 – REGULATORY INFORMATION

LAND - DOT	UN/NA IDENTIFICATION NUMBER, UN-PROPER SHIPPING NAME, TRANSPORT HAZARD CLASS, PACKING GROUP, MARINE POLLUTANT, HAZARD CLASS,	Not Applicable to unused finished product
WATER - IMO/IMDG	UN/NA IDENTIFICATION NUMBER, UN-PROPER SHIPPING NAME, TRANSPORT HAZARD CLASS, PACKING GROUP, MARINE POLLUTANT.	Not Applicable to unused finished product
AIR – ICAO/IATA For product quantities less than 0.5 Kg	UN/NA IDENTIFICATION NUMBER, UN-PROPER SHIPPING NAME, TRANSPORT HAZARD CLASS, PACKING GROUP, MARINE POLLUTANT.	Not Applicable to unused finished product

SECTION 15 - OTHER INFORMATION

THE INFORMATION AND RECOMMENDATIONS CONTAINED IN THIS DOCUMENT ARE PROVIDED FREE WITHOUT CHARGE SOLELY FOR TRAINED, QUALIFIED, TECHNICALLY COMPETENT, AND PROFESSIONAL COMMERCIAL INDUSTRIAL, MILITARY, OR GOVERNMENT USERS AT THEIR DISCRETION AND RISK. ALL STATEMENTS INFORMATION, AND RECOMMENDATIONS CONTAINED IN THIS DOCUMENT ARE BASED UPON DATA AND OTHER NFORMATION THAT CHEMTEQ BELIEVE TO BE CORRECT AND COMPLETE AS OF THE DATE ISSUED. BUT THE ACCURACY AND COMPLETENESS THEREOF IS NOT GUARANTEED AND NO WARRANTY OF ANY KIND IS MADE WITH RESPECT TO THE INFORMATION OR RECOMMENDATIONS CONTAINED IN THIS DOCUMENT. THE USER IS RESPONSIBLE FOR DETERMINING WHETHER THE PRODUCT OR COMPONENT IS FIT FOR A PARTICULAR PURPOSE AND SUITABLE FOR THE USER'S METHOD OF USE OR APPLICATION. GIVEN THE VARIETY OF FACTORS THAT CAN AFFECT THE USE AND APPLICATION OF A PRODUCT OR COMPONENT, SOME OF WHICH ARE UNIQUELY WITHIN THE USER'S KNOWLEDGE OR CONTROL, IT IS ESSENTIAL THAT THE USER EVALUATE THE PRODUCT OR COMPONENT TO DETERMINE WHETHER THE PRODUCT OR COMPONENT IS FIT FOR A PARTICULAR PURPOSE AND ADDITIONALLY SUITABLE FOR USER'S METHOD OF USE OR APPLICATION AND SUITABLE FOR THE TEST SUBJECT. REASONABLE CARE HAS BEEN TAKEN IN THE PREPARATION OF THIS INFORMATION HOWEVER, CHEMTEQ MAKES NO WARRANTY OF MERCHANTABILITIY OR ANY OTHER WARRANTY, EXPRESSED DR IMPLIED WITH RESPECT TO THIS INFORMARION. CHEMTEQ MAKES NO REPRESENTATION AND ASSUMES NO LIABILITY FOR ANY DIRECT, OR INDIRECT OR CONSEQUENTIAL DAMGES RESULTING FROM ITS USE.