

WearGuard™

Performance Engineered Lubricants

D-A SYN Compressor Flush



Product Description

WearGuard™ D-A SYN Compressor Flush is a premium quality synthetic fluid designed to dissolve varnish and solubilize sludge from rotary-screw air compressors during operation. It can also be used as a system flush when changing-over from mineral to synthetic oils in order to reduce contamination due to oil carry-over. Regular use of **WearGuard™ D-A SYN Compressor Flush** will help you get the most out of your synthetic oil and your compressor by removing varnish and reducing operating temperature.

Product Features and Benefits

- 100% Synthetic Lubricant

- Solubilizes and removes harmful varnish and sludge

- Contains additives – can be used as a lubricant for up to 500 hours

- Contains no aromatic solvents or hazardous chemicals

- Compatible with mineral oils as well as synthetic oils

- USDA H-2 authorized

- High flash point

- May adversely affect some paint finishes, plastics and seals

Typical Applications

Rotary Screw Compressors
Rotary Vane Compressors
Centrifugal Compressors

Typical Properties

| | | |
|---------------------------|-------------|-----------|
| ISO Viscosity Grade | Test Method | 32 |
| Viscosity @ 100°C, cSt | ASTM D445 | 6.5 |
| @ 40°C, cSt | ASTM D445 | 37.1 |
| Viscosity Index | ASTM D2270 | 126 |
| Pour Point, °F (°C) | ASTM D97 | -49 (-45) |
| Flash Point, °F (°C) | ASTM D92 | 400 (204) |
| API Gravity | ASTM D4052 | 19 |
| Copper Strip Corrosion | ASTM D130 | 1b |

D-A Part Number:

Bulk

IP72511

Tote – 330 Gal

IP72513

Pail (Plastic) – 5 Gal

IP72518