# Articulated side guides

Technopolymer, stainless steel













### SELF-SUPPORTING STRUCTURE

Acetal resin based (POM) technopolymer, black colour.

# PINS

AISI 304 stainless steel.

#### ROLLERS

Polyethylene based (PE) technopolymer, grey colour.

# STANDARD EXECUTIONS

- GLB-1-RS: with spherical contact rollers.
- GLB-1-RC: with cylindrical contact rollers.
- GLB-1-RT: with round contact rollers.

# FEATURES AND APPLICATIONS

GLB-1 side guides are modular self-supporting structures for the side guide of products with limited vertical dimensions on conveyor belts (Fig.1).

Particularly suitable for use in wet environments.

Depending on the product to transport, it is recommended to use:

- GLB-1-RS: for the guide of products in cans or in plastic containers;
- GLB-1-RC: for the guide of cardboard products, for a greater fluency;
- GLB-1-RT: for the guide of glass products, in case of accidental breakage they facilitate the expulsion of debris.

The joint in the roller side guides allows an external curvature radius 500 mm, internal curvature radius 350 mm.

Supplied already assembled in modules of 375 mm length, for profiles 40 x8 mm.




- Side guides with self-supporting structure and rollers in different colours.
- Side guides with pins in acetal resin based (POM) technopolymer.


# ACCESSORIES ON REQUEST

- PRA-GLB: AISI 304 stainless steel profile for side guides.
- PRB-GLB: AISI 304 stainless steel profile for side guides.









Levelling elements and supports





























85







INOX STAINLESS METRIC

 $\Delta \Delta$ 

340






GLB-1-RS Code

419161


Description

GLB-1-RS-46-375

GLB-1-RC				
Ų,		<b>L</b>		
i				
1				



.12.5	LB-1-RT
13.5	



INOX STAINLESS STEEL	METRIC )
Description	Δ'Δ
GLB-1-RT-46-375	340
	Description