



Main

Product	Lug kit
Provided equipment	Screw set 1 Lug 4

Complementary

Material	Aluminium
Current Rating	250 A
Tightening torque	60.18...64.61 Lbf.In (6.8...7.3 N.m) 0.02...0.27 in ² (13.3...177.3 mm ²) (AWG 6...350 kcmil) 24.78...30.09 lbf.in (2.8...3.4 N.m)

Environment

Product certifications	CULus
------------------------	-------

Ordering and shipping details

Category	08338 - NF (& SHARED) RTI ACCESSORIES
Discount Schedule	PE1A
GTIN	00785901538691
Nbr. of units in pkg.	1
Package weight(Lbs)	1 lb(US) (0.45 kg)
Returnability	Yes
Country of origin	US

Packing Units

Package 1 Height	2.30 in (5.842 cm)
Package 1 width	14.40 in (36.576 cm)
Package 1 Length	20.70 in (52.578 cm)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Bisphenol A (BPA), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
RECh Regulation	RECh Declaration
RECh free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes

RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration

Contractual warranty

Warranty	18 months
----------	-----------
