9001KP1C31 PILOT LIGHT 120VAC 30MM TYPE K +OPTIONS





Main	
Range of product	Harmony 9001K
Product or component type	Pilot light

Complementary

Bezel material	Chromium plated metal	_
Mounting diameter	1.18 in (30 mm)	
Lens type	Fresnel plastic	
Cap/operator or lens colour	Clear	
Light source	incandescent	
Bulb base	BA 9s	
Light block supply	Via transformer 120 V AC 50/60 Hz Via integral transformer 110 V AC 50/60 Hz	
Connections - terminals	Screw clamp terminals, 1 x 0.222 x 1.5 mm² IEC 60947-1	
Shape of screw head	Round	
Operating position	Any position	
[Us] rated supply voltage	110120 V AC	
Operating mode	Normal	
Device presentation	Complete product	

Device short name

Environment

Product certifications	CE	
	UL listed file E42259 CCN NKCR	
	CSA LR25490 class 3211 03	
NEMA degree of protection	NEMA 1/2/3/3R/4/6/12/13	

Ordering and shipping details

21426 - 9001 K (NOT KA,KM,KX)	
CS1	
00785901032045	
1	
0.5 lb(US) (0.23 kg)	
No	
MX	
	CS1 00785901032045 1 0.5 lb(US) (0.23 kg) No

Packing Units

Package 1 Height	5.08 in (12.903 cm)
Package 1 width	2.00 in (5.080 cm)
Package 1 Length	12.90 in (32.774 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	₫Yes
China RoHS Regulation	☑ China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Contractual warranty