
American Standard

Style That Works Better

QUENTIN[™] SINGLE CONTROL LAVATORY FAUCET



GENERAL DESCRIPTION:

Brass swivel spout. (Spout can be locked, if desired). Metal Lever handle. Washerless 28mm ceramic disc valve cartridge. Braided flexible supply hoses with 3/8" compression connectors. 20 inch (500mm) long flexible stainless steel drain cable is pre-assembled to spout. Metal Speed Connect[®] drain body with 1-1/4 inch (32mm) tail piece. 1.5 gpm/5.7L/min. maximum flow rate. Fitting can be mounted on 4" centers using optional escutcheon (2000.102P) or single hole mounting method.

PRODUCT FEATURES:

Brass Swivel Spout: Durable. Easy to clean. Ideal for prolonged contact with water.

Ceramic Disc Valve Cartridge: Assures a lifetime of smooth handle operation and drip-free performance.

Lead Free: Faucet contains $\leq 0.25\%$ total lead content by weighted average.

Exclusive Speed Connect Metal Drain:

- Fewer parts. Installs in less time.
- No adjustments required seals the first time, every time.
- Flexible stainless steel cable installs effortlessly in tight spaces.

Choice of Finishes: Wide range of durable finishes.

SUGGESTED SPECIFICATION:

Single control lavatory faucet shall feature a brass swivel spout and metal lever handle. Shall also feature washerless ceramic disc valve cartridge. Shall also feature a metal drain body with stainless steel cable actuation. Fitting shall be American Standard Model # 7440.101.____.




Style That Works Better

QUENTIN[™] SINGLE CONTROL LAVATORY FAUCET

CODES AND STANDARDS

These products meet or exceed the following codes and standards:

ANSI A117.1 ASME A112.18.1 NSF 61/Section 9 and Annex G CSA B 125.1



			Finish Options		
Product		Polished Chrome	Oil Rubbed Bronze	PVD Satin Nickel	
Number	Description	002	224	295	
7440.101	Quentin single control lavatory faucet. Metal Speed Connect [®] Pop-up drain.				
2000.102P	Optional Escutcheon Plate Only (For Mounting on 4" Centers)				

Meets the American Disabilities Act Guidelines and **ANSI A117.1** Requirements for the physically challenged.