EE75S3H TRFMR DRY 1HP 75KVA 240X480V-120/240V





Main

Product	Energy Efficient Transformer
Enclosure Code	21D
Enclosure Type	NEMA 2
Insulation Temperature	428 °F (220 °C)
Phase	1 phase
Primary Voltage	240 x 480 V
Power Rating	75 kVA
Secondary Voltage	120/240 V
Full Capacity Taps	6 2.5 % 2+ 4-
Temperature Rise	150 °C
Winding Material	Aluminium

Ordering and shipping details

Category	16284 - 1 PH EE/TP1 LVGP XFMR	
Discount Schedule	PE2E	
GTIN	00785901629665	
Nbr. of units in pkg.	1	
Package weight(Lbs)	1 lb(US) (0.45 kg)	
Returnability	Yes	
Country of origin	MX	

Packing Units

Package 1 Height	3.50 ft (1.067 m)	
Package 1 width	2.34 ft (0.714 m)	
Package 1 Length	2.75 ft (0.838 m)	

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Phenyl Glycidyl Ether, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EPEU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	₫Yes
China RoHS Regulation	☑ China RoHS Declaration
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty	18 months