
NF250SFL

NF Panelboard Acc. Subfeed Lug Kit 250A, Aluminum

Main





Complementary

Current Rating	250 A
Tightening torque	60.1864.61 lbf.in (6.87.3 N.m) 0.020.27 in² (13.3177.3 mm²) (AWG 6350 kcmil)

Environment

|--|

Ordering and shipping details

Category	08338 - NF (& SHARED) RTI ACCESSORIES	
Discount Schedule	PE1A	
GTIN	00785901700517	
Nbr. of units in pkg.	1	
Package weight(Lbs)	1 lb(US) (0.45 kg)	
Returnability	Yes	
Country of origin	US	
Country or origin		

Packing Units

Package 1 Height	3.20 in (8.128 cm)
Package 1 width	4.20 in (10.668 cm)
Package 1 Length	7.90 in (20.066 cm)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Bisphenol A (BPA), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EPEU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	₫Yes
China RoHS Regulation	☑ China RoHS Declaration

Warranty 18 months