



Main

Product or component type	Industrial Control Transformer
Power Rating	200 VA
Primary Voltage	208 V
Secondary Voltage	120 V
Type	TF

Complementary

Number of Phases	1 phase
Power Rating	200 VA
Primary to Secondary Voltage	208 V 120 V
Fuse type	0.41 x 1.50 in CC top
Temperature rise	80 °C
Electrical connection	Screw clamp terminals
Height	4.5 in (114.30 mm)
Width	3.75 in (95.25 mm)
Depth	3.59 in (91.19 mm)
Material	Copper winding
Fingersafe Cover Compatibility	FSC1

Environment

Product certifications	CSA file LR37055 guide 184-N-90 UL listed file E61239
Enclosure Type	Not rated (open device)
Insulation temperature	266 °F (130 °C)

Ordering and shipping details

Category	16202 - 9070 TF (NOT T) 50-200VA
Discount Schedule	CP8
GTIN	00785901391593
Nbr. of units in pkg.	1
Package weight(Lbs)	5.9 lb(US) (2.68 kg)
Returnability	Yes
Country of origin	US

Packing Units

Package 1 Height	6.60 in (16.764 cm)
Package 1 width	6.70 in (17.018 cm)
Package 1 Length	7.70 in (19.558 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Phenyl glycidyl ether, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
PVC free	Yes

Contractual warranty

Warranty	18 months
----------	-----------