



## Main

Power Rating	100 VA
Primary Voltage	550 V 600 V 575 V
Secondary Voltage	110 V 115 V 120 V
Type	TF

## Complementary

Fuse type	0.41 x 1.50 in CC top
Temperature rise	55 °C
Height	4.25 in (107.95 mm)
Width	3.38 in (85.85 mm)
Depth	3.34 in (84.84 mm)
Material	Copper winding

## Environment

Product certifications	CSA file LR37055 guide 184-N-90 UL listed file E61239
Insulation temperature	221 °F (105 °C)

## Ordering and shipping details

Category	16202 - 9070 TF (NOT T) 50-200VA
Discount Schedule	CP8
GTIN	00785901736790
Nbr. of units in pkg.	1
Package weight(Lbs)	4.5 lb(US) (2.04 kg)
Returnability	Yes
Country of origin	MX

## Packing Units

Package 1 Height	6.20 in (15.748 cm)
Package 1 width	7.00 in (17.780 cm)
Package 1 Length	8.10 in (20.574 cm)

## Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Phenyl glycidyl ether, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
PVC free	Yes

## Contractual warranty

Warranty	18 months
----------	-----------