

**Garant**
**GARANT Master Tap INOX machine tap HSS-E-PM, TiAlN, UNF: 1/4-28**

**Order data**

Order number	138007 1/4-28
GTIN	4062406210212
Item class	111

**Description**
**Version:**
**GARANT Master Tap INOX:**

High-performance tap, specially developed for **good process reliability in stainless and acid-resistant steels** and **duplex materials**.

**The 45° helix angle** of the chip flutes facilitates chip formation especially in ductile austenitic CrNi steels.

- **HSS-E-PM tool material for maximum wear resistance**
- **The latest generation of TiAlN multi-layer coating**
- **Parameterised flute geometry for optimum chip formation and torsional rigidity**

**Application:**

**For UNF uniform fine threads** ASME – B1.1.

Thread type: UNF

Tool material: HSS E PM

Standard: DIN 371

Threads per inch: 28

Thread Ø: 6.35 mm

Overall length L: 80 mm

Shank Ø D<sub>s</sub>: 7 mm

Shank square □: 5.5 mm

Tapping hole Ø: 5.5 mm

**Technical description**

Number of clamping slots	3
Tool material	HSS E PM
Tapping hole Ø	5.5 mm

Thread Ø	6.35 mm
Thread pitch	0.907 mm
Overall length L	80 mm
Thread depth	15.9 mm
Shank Ø D <sub>s</sub>	7 mm
Thread size	1/4-28 UNF
Number of cutting edges Z	3
Standard	DIN 371
Threads per inch	28
Thread type	UNF
Shank square □	5.5 mm
Series	Master Tap
Coating	TiAlN
Flank angle	60°
Tolerance class	2BX
Taper lead form	C
Helix angle	45°
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 2.5×D for blind holes
Cutting direction	right-hand
Type of threading tool	Machine tap for dynamic machining
Colour ring	blue
Type of product	Tap

## User data

	Suitability	V <sub>c</sub>	ISO code
Aluminium (short chipping)	suitable only under restricted conditions	28 m/min	N

Steel < 750 N/mm <sup>2</sup>	suitable only under restricted conditions	23 m/min	P
Steel < 900 N/mm <sup>2</sup>	suitable only under restricted conditions	23 m/min	P
Steel < 1100 N/mm <sup>2</sup>	suitable	12 m/min	P
INOX < 900 N/mm <sup>2</sup>	suitable	11 m/min	M
INOX > 900 N/mm <sup>2</sup>	suitable	9 m/min	M
Oil	suitable		
wet maximum	suitable		