Garant

Torque screwdriver, fixed setting, set torque: 0,45N·m



Order data

Order number	211750 0,45
GTIN	4045197607584
Item class	21B

Description

Version:

Torque screwdriver with easy-grip 2-component T-handle. The torque is fixed. Toolholder with permanent magnet.

Function:

When the torque is reached the screwdriver triggers **with clearly audible and perceptible signal**. The long-travel indication gives the user an unmistakable signal that the set torque has been reached.

Application:

In conjunction with **1/4 inch bits** with **C 6.3** or **E 6.3 shank,** e.g. **Torx Plus**[®] **bit** No. **674252.** Ideal for precise tightening of indexable inserts to the specified torque.

Standard:

Geprüft nach DIN EN ISO 6789.

Note:

Supplied **without** bit.

The guaranteed measuring accuracy of the torque is achieved only once the torque range has been calibrated to DIN EN ISO 6789.

Direction of tightening: Right-hand tightening

Torque measuring accuracy: ±15 %

Bit socket: D 6,3

Bit socket: F 6.3

Data sheet

Torque measuring accuracy: $\pm 15 \%$ Overall length L: 107 mm Blade length: 50 mm set torque: 0.45 N·m

Technical description

Blade length	50 mm
Torque measuring accuracy	±15 %
set torque	0.45 N·m
Bit socket	D 6,3
Bit socket	F 6.3
Setting the trigger value	preset
Overall length L	107 mm
Standard	DIN EN ISO 6789
Connection format	Bit holder 1/4 inch
Reversible reading	Nm
Measurement process	Torque
Trigger principle	Mechanical long travel release
Adjustable trigger value	non-adjustable
Feedback	triggering
Direction of tightening	Right-hand tightening
Data can be recorded	no
Measurement technology	mechanical
Release signalling	akustisk
Release signalling	haptisk
Type of product	Torque screwdriver

Accessories

"TQ-Station" – storage station for torque screwdrivers

659964

© Hoffmann GmbH Qualitätswerkzeuge