

Abrasive fleece pad, 152×229 mm, Fleece structure: 1000



Order data

Order number	556015 1000
GTIN	4045197542434
Item class	52M

Description

Version:

Synthetic nylon fleece impregnated with abrasive grit in synthetic resin bonding.

Advantage:

- · Adapts to the component shape.
- · The open structure prevents clogging and reduces heat development.
- · Even and reproducible finish.
- · Can be used wet or dry.
- · Contains no materials that could cause corrosion.

Application:

Can be used by hand, on hand block No. 556020 or on an orbital sander. **Fine / very fine:** for cleaning delicate surfaces, for removing light scratches on metals. Also suitable for applying fine / very fine matt finishes to steels and non-ferrous metals.

Iron, sulphur and chlorine constituents: < 0.1 %

Grit equivalent: 600 - 1000 Grit designation: very fine

Version: S Ultra Fine

Colour: grey

Technical description

Colour	grey
Fleece structure	1000
Grit designation	very fine



Grit equivalent	600 - 1000	
Version	S Ultra Fine	
Iron, sulphur and chlorine constituents	< 0.1 %	
Width	152 mm	
Length	229 mm	
Product name attribute	152×229 mm	
Type of product	Abrasive fleece pad	

User data

	Suitability	\mathbf{V}_{c}	ISO code
Alu Mg	suitable		
Steel < 900 N/mm ²	suitable		
Steel < 1400 N/mm ²	suitable		
Steel < 55 HRC	suitable		
Steel < 60 HRC	suitable		
Steel < 67 HRC	suitable		
INOX	suitable		
Ti	suitable		
GG(G)	suitable		
CuZn	suitable		
Plastic, GRP	suitable		
Wood	suitable		
Stone	suitable only under restricted conditions		
Paint	suitable		
Uni	suitable		
wet maximum	suitable only under restricted conditions		
dry	suitable		



Accessories

Hand block	556020
Mandrel	556030