

# **GARANT Master Tap machine tap HSS-E-PM, AITIX, UNC: 7/8-9**



## **Order data**

Order number	133360 7/8-9
GTIN	4045197901743
Item class	111

## **Description**

#### **Version:**

**GARANT Master Tap universal taps**, designed for use in a wide spectrum of materials with high process reliability.

- · HSS-E-PM tool material for maximum wear resistance.
- · Reduced coefficient of friction due to the new high-performance coating.
- · Special geometry for optimum swarf evacuation.

### **Application:**

**For UNC uniform coarse threads** ASME – B1.1.

Thread type: UNC

Tool material: HSS E PM Standard: DIN 376 Threads per inch: 9 Thread Ø: 22.23 mm Overall length L: 140 mm Shank Ø D<sub>s</sub>: 18 mm

Shank square  $\square$ : 14.5 mm Tapping hole  $\varnothing$ : 19.5 mm

# **Technical description**

Tapping hole ∅	19.5 mm
Thread Ø	22.23 mm
Threads per inch	9
Shank Ø D <sub>s</sub>	18 mm
Number of cutting edges Z	3

Overall length L	140 mm		
Standard	DIN 376		
Number of clamping slots	3		
Thread depth	66.69 mm		
Thread pitch	2.822 mm		
Shank square □	14.5 mm		
Thread type	UNC		
Tool material	HSS E PM		
Thread size	7/8-9 UNC		
Series	Master Tap		
Coating	AlTiX		
Flank angle	60 °		
Tolerance class	2BX		
Taper lead form	В		
Shank	Plain shank with h9		
Through-coolant	no		
Application for type of drilling	up to 3×D for through holes		
Cutting direction	right-hand		
Type of threading tool	Machine tap for dynamic machining		
Colour ring	green		
Type of product Tap			

# **User data**

	Suitability	$\mathbf{V}_{c}$	ISO code
Alu plastics	suitable	30 m/min	N
Aluminium (short chipping)	suitable	35 m/min	N
Alu > 10% Si	suitable	20 m/min	N
Steel < 500 N/mm <sup>2</sup>	suitable	30 m/min	Р

Steel < 750 N/mm <sup>2</sup>	suitable	30 m/min	Р
Steel < 900 N/mm <sup>2</sup>	suitable	25 m/min	Р
Steel < 1100 N/mm <sup>2</sup>	suitable	12 m/min	Р
Steel < 1400 N/mm <sup>2</sup>	suitable	8 m/min	Р
INOX < 900 N/mm <sup>2</sup>	suitable	10 m/min	М
INOX > 900 N/mm <sup>2</sup>	suitable	8 m/min	М
GG(G)	suitable	20 m/min	K
CuZn	suitable	20 m/min	N
Uni	suitable		
Oil	suitable		
wet maximum	suitable		