

Garant
GARANT Master Tap machine tap HSS-E-PM, ALTiX, UNC: 7/8-9

Order data

Order number	137870 7/8-9
GTIN	4045197901620
Item class	111

Description
Version:

GARANT Master Tap Universal tap, designed for use in a wide spectrum of materials with high process reliability.

- **HSS-E-PM tool material for maximum wear resistance.**
- **Reduced coefficient of friction due to the new high-performance coating.**
- **Special geometry for optimum swarf evacuation.**

Application:

For UNC uniform coarse threads ASME – B1.1.

Thread type: UNC

Tool material: HSS E PM

Standard: DIN 376

Threads per inch: 9

Thread Ø: 22.23 mm

Overall length L: 140 mm

Shank Ø D_s: 18 mm

Shank square □: 14.5 mm

Tapping hole Ø: 19.5 mm

Technical description

Thread size	7/8-9 UNC
Shank Ø D _s	18 mm
Overall length L	140 mm
Thread Ø	22.23 mm

Thread type	UNC
Number of cutting edges Z	4
Thread pitch	2.822 mm
Thread depth	55.56 mm
Tool material	HSS E PM
Number of clamping slots	4
Standard	DIN 376
Tapping hole Ø	19.5 mm
Threads per inch	9
Shank square □	14.5 mm
Series	Master Tap
Coating	AlTiX
Flank angle	60 °
Tolerance class	2BX
Taper lead form	C
Helix angle	40 °
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 2.5×D for blind holes
Cutting direction	right-hand
Type of threading tool	Machine tap for dynamic machining
Colour ring	green
Type of product	Tap

User data

	Suitability	V _c	ISO code
Alu plastics	suitable	30 m/min	N
Aluminium (short chipping)	suitable	35 m/min	N

Alu > 10% Si	suitable	20 m/min	N
Steel < 500 N/mm ²	suitable	30 m/min	P
Steel < 750 N/mm ²	suitable	30 m/min	P
Steel < 900 N/mm ²	suitable	25 m/min	P
Steel < 1100 N/mm ²	suitable	12 m/min	P
Steel < 1400 N/mm ²	suitable only under restricted conditions	8 m/min	P
INOX < 900 N/mm ²	suitable	10 m/min	M
INOX > 900 N/mm ²	suitable	8 m/min	M
GG(G)	suitable	20 m/min	K
CuZn	suitable	20 m/min	N
Uni	suitable		
Oil	suitable		
wet maximum	suitable		