













PIG® Water-Activated Flood Bag

WTR010 Ideal For Stacking, Retaining Walls,12" W x 24" L x 3.5" H When Fully Saturated, 36 per bag

Super absorbent flat bags swell on contact with water to form a solid, heavy barrier to quickly dam and divert floodwater.

- Sandbag alternatives are lightweight, compact and easy to handle prior to activation; place in flood-prone areas when you know water is coming
- Sandless solution eliminates the mess, heavy lifting and manual labor of filling standard bags with 40 lbs. of sand
- Stack and stagger sandbag replacements up to three rows high; build even higher retaining walls by using a pyramid layout
- NOTE: Not for use with salt water

Specifications

Dimensions	15" W x 26" L x .25" H
Brand	PIG
Capacity	4 gal. per Bag
Dimensions When Fully Saturated	12" W x 24" L x 3.5" H When Fully Saturated
Height When Fully Saturated	3.5" When Fully Saturated
Ideal For	Stacking, Retaining Walls
Color	Black
Install/Deploy Type	Temporary/Removable Barrier
Temperature Limit	Works from 32°F to 180°F
Traffic	Non-Weight Bearing
Weight When Fully Saturated	32 lbs. each When Fully Saturated
Sold as	36 per bag
Weight	17.5 lbs.
# per Pallet	56
Composition	Skin: Polypropylene Filler: Super Absorbent Polymer (SAP)
UNSPSC	24101907
Pigalog® Page Number	Page 261

Metric Equivalent

Weight 7.9 kg

Technical Information

Technical Documents

FAQ for PIG Water-Activated Flood Bags & Barriers

Instructions for PIG Water-Activated Flood Bags & Barriers

Technical Data Sheet for PIG® Water-Activated Flood Bag & Barrier



One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com