





		ELEMENT SPECS			
ĺ	PART NUMBER 375P				
	MATERIAL	Poly	ester		
	FLOW RATE	1500 CFM	2549 m³/hr		
	SURFACE AREA	28.0 ft ²	2.6 m ²		
	I.D.	SEE DRAWING	SEE DRAWING		
	O.D.	SEE DRAWING	SEE DRAWING		
	HEIGHT	SEE DRAWING	SEE DRAWING		



THE INFORMATION CONTAINED HEREIN IS CONFIDENTIAL AND THE PROPERTY OF SOLBERG MANUFACTURING INC. AND IT IS FURNISHED TO YOU WITH THE EXPRESS UNDERSTANDING THAT IT WILL NOT BE REPRODUCED, COPIED IN ANY MANNER, LOANED OR OTHERWISE TRANSFERRED TO OTHERS ENTIRELY OR IN PART, NOR USED FOR ANY PURPOSE OTHER THAN FOR WHICH IT WAS FURNISHED. IT WILL BE RETURNED UPON REQUEST TO SOLBERG MANUFACTURING INC. THE ABOVE RESTRICTION IS IN ADDITION TO, AND DOES NOT IN ANY WAY ALTER, ANY OTHER RESTRICTIONS WHICH MAY APPLY TO THE INFORMATION CONTAINED HEREIN.

TOLERANCES

DIMENSIONS ARE FOR REFERENCE ONLY.
ALL DIMENSIONS ARE SUBJECT TO CHANGE
DESCRIPTION: 375P, POLY **UPON PRODUCTION.**

UNLESS OTHERWISE SPECIFIED:
-DIMENSIONS ARE IN INCHES
-REF: APPROXIMATE DIMENSIONS, NO TOLERANCES APPLY
-FINISH: BREAK EDGES TO .005-.020 RADIUS/CHAMFER

MODEL NUMBER: 375P	SHEET:
WODEL NOWBER. 3/3F	1 OF 1

DESCRIP	HON.	31	3F	, г	OL

ROJECT:	DRAWN BY: CRW	APPROVED BY: M.C.	REV:
	DATE : 6/12/2014	DATE : 6/12/2014	