

# **Technical Sheet**

# **Product**

**Premium Thin Aluminium Oxide Wheels** 

Type1 Premium Thin Aluminium Oxide Wheels Double reinforced

# 1. Description of Product

| Dimensions(in): | 3" X 1/16" X 3/8"     |
|-----------------|-----------------------|
| Max RPM:        | 24,465                |
| Abrasive:       | STEEL STAINLESS STEEL |
| Line:           | ULTICUT               |
| Part Number:    | AU2-10300621          |















## 1. Application

 Designed for hard and continuous cutting through all masonry types.

### 2. Operating instructions

- Use on an angle grinder.
- Mount the disc and let it idle for one minute to check that it is not damaged.
- Keep the blade at 90 ° from the work surface.
- Do not press excessively, or hit against the backing material job.

#### 3. Safety information

- Before mounting or dismounting the disc, check that the machine is disconnected.
- Never exceed the maximum peripheral speed marked on the label.
- Always use security guards.
- It is recommended to use full safety equipment (gloves, hearing protection, mask and safety glasses).
- Never try to make curved cuts.
- Never use a disc that has gotten wet.
- Do not use for roughing operations.

- Do not use the disc in machines for which it was not designed.
- Improper use can cause severe injury.
- Use as directed by ANSI B7.1.

## 4. Handling

• Handle discs with care to prevent bumps or drops. Yes a disc falls, fractures, detaches a section or is suspect that it may have damage, it should not be mounted.

#### 5. Storage

- Store discs on a flat surface and do not hit or hit them. I dropped them.
- The discs must not be exposed to:
- (a) Water or other solvents.
- (b) Extreme temperatures or humid conditions.
- For more information, consult the ANSI B7.1 standard.

#### 6. Packaging units

- Box Quantity: 50
- Case Quantity: 800

