

Features

- Includes faceplate and lever handle.
- Single handle controls both on/off activation and temperature settings.
- Pressure-balancing diaphragm technology maintains outlet temperature within +/-3°F during water pressure fluctuations.
- Provides anti-scald protection and temperature regulation.
- Supplied with metal Industrial handle.
- Coordinates with Components faucets, accessories, and showering components to complete your bathroom.

Material

- Premium material construction with metal handle ensures reliability and durability.
- KOHLER finishes resist corrosion and tarnishing.

Installation

Trim only; requires valve to complete installation (sold separately).

Required Products/Accessories

K-2971-KS 3/4" Pressure-balancing Valve

or

K-8300-KS Valve Body Rough-In K-8304-KS Valve Body & Cartridge Kit Complete

or

K-P8300-KS Valve Body Rough-In K-P8304-KS Valve Body & Cartridge Kit Complete

Adapters, Rough-in and Extension Kits

10350

Range: 3-5/8" (92 mm) -4-3/8" (111 mm)

Recommended Products/Accessories

K-23723 Faucet cleaner





Codes/Standards

ASME A112.18.1/CSA B125.1 ADA ICC/ANSI A117.1 CSA B651 OBC

KOHLER[®] Faucet Lifetime Limited Warranty

See website for detailed warranty information.

Available Colors/Finishes

Color tiles intended for reference only.


Color	Code	Description
	CP	Polished Chrome
in the second	BN	Vibrant® Brushed Nickel
	BL	Matte Black
	2MB	Vibrant® Brushed Moderne Brass



Components™ Rite-Temp[®] shower valve trim K-TS78015-4

KOHLER, Faucets

Components™ Rite-Temp® shower valve trim K-TS78015-4



Technical Information

All product dimensions are nominal. Drain included: No

Notes

Install this product according to the installation instructions.

NOTICE: Risk of product damage. Long screws for installing trim can damage the K-2971-KS valve. Consult the trim installation guide to verify if the thin wall installation kit is needed.

Install straight pipe or tube drop of 7" (178 mm) to 18" (457 mm) with single elbow between the valve and the wall-mount spout.

ADA, OBC, CSA B651 compliant when installed to the specific requirements of these regulations.

