

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: [0638238370](#)
Status: **Active**
Overview: [Application Tooling](#)
Description: Modular Crimp Head for Hand Crimp Tool for 6.35mm Tab Slip-on Male Crimp Terminals
Replacement Part Number : <http://www.molex.com/molex/search/partSearch?pQuery=&sType=p&query=0638238300638238300>

Documents:

[RoHS Certificate of Compliance \(PDF\)](#)

General

Product Family	Application Tooling
Series	207129
Comments	See Tooling Specification (PDF) Above; Modular Crimp Heads are not sold separately; the complete hand tool needs to be ordered to obtain a See Tooling Specification (PDF) Above; Modular Crimp Head 638238300; Type: TOOL KIT
Function	Crimp
Geographic Area	Global
Level of Automation	Manual
More Detailed Tech Information	applicationtooling@molex.com
Overview	Application Tooling
Product Name	PremiumGrade
Replacement Part Number	638238300
Taxonomy	Applicators and Crimp Modules
Tool Type	Crimp Module
UPC	884982481053
Warranty Disclaimer	CAUTION: Molex tooling crimp specifications are valid only when used with Molex terminals and tooling manufactured by Molex and sold by Molex or authorized distributors ("Molex Tooling"). When using tooling other than Molex Tooling with Molex specific connector systems listed in our ATS documents, the Molex tooling qualification does not apply and the responsibility for full qualification of the connector system is that of the customer. Molex accepts no liability for connector performance or tooling support where tooling other than Molex Tooling is used or where Molex Tooling is modified.

Material Info

Reference - Drawing Numbers

Application Tooling Documents [ATS-6382383HM-001](#)



EU ELV

Not Reviewed

EU RoHS

Not Reviewed

REACH SVHC

Not Reviewed

Halogen-Free

Status

Not Reviewed

For more information, please visit [Contact US](#)

China ROHS

Not Reviewed

ELV

Not Reviewed

RoHS Phthalates

Not Reviewed

Search Parts in this Series

[207129](#) Series

Use With

[35725](#) 6.35mm Tab Slip-on Male Crimp Terminals, 20-22 AWG, 0.30-0.50mm² wires