

**PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION**

**Part Number:** [130000090](#)  
**Status:** **Active**  
**Overview:** Brad Quick-Change Connectors  
**Description:** Quick-Change Single-Ended Cordset, 4 Poles, Female (Straight) to Pigtail, 12 AWG, Yellow CPE Cable, 3.66m (12.0') Length

**Documents:**

[Drawing \(PDF\)](#) [RoHS Certificate of Compliance \(PDF\)](#)

**Agency Certification**

CSA LR6837  
 UL E46237

**General**

Product Family Industrial Cordsets  
 Series [130000](#)  
 Connector End A Quick-Change  
 Connector End B Pigtail  
 IP Rating IP67  
 Material - Contact Copper Alloy  
 Overview [Brad Quick-Change Connectors](#)  
 Product Name Quick-Change  
 Region America  
 Taxonomy Circular Industrial Cordsets  
 Type Single Ended  
 UPC 78678832679

**Physical**

Cable Diameter 18.03mm (.710")  
 Cable Length 3.66m (12.0')  
 Color - Cable Jacket Yellow  
 Coupling Style Threaded  
 Gender Female-Pigtail  
 Keyway Single  
 LED Indicator No  
 Material - Cable Jacket CPE  
 Material - Connector Body TPE  
 Material - Coupling Nut Nylon  
 Material - Plating Mating N/A  
 Net Weight 1623.861/g  
 Orientation Straight to Pigtail  
 Poles 4  
 Temperature Range - Operating -20° to +105°C  
 Wire Size AWG 12  
 Wire/Cable Type SOW

**Electrical**

Current - Maximum per Contact 20.0A  
 Voltage - Maximum 600V

**Material Info**

Engineering Number 32679

**Reference - Drawing Numbers**

Sales Drawing SD-130000-005-001



*Series image - Reference only*

**EU ELV**

**Not Relevant**

**EU RoHS**

**Compliant with Exemption 6(c)**

**REACH SVHC**

Not Reviewed

**Halogen-Free**

**Status**

**Not Reviewed**

For more information, please visit [Contact US](#)

China ROHS

ELV

RoHS Phthalates

ZZCERT\_UKCA

- Declaration of

Conformity

**China RoHS**

50 Image

Not Relevant

Not Contained

CER\_4000410542\_00\_000.pdf

**Search Parts in this Series**

[130000 Series](#)

This document was generated on 10/17/2022

**PLEASE CHECK [WWW.MOLEX.COM](http://WWW.MOLEX.COM) FOR LATEST PART INFORMATION**