

## • Products

- O By Type
  - Connectors
  - Electromechanical Components
  - Electronic Modules
  - Fiber Optics
  - Filters
  - Identification & Labeling
  - Passive Components
  - Power Sources
  - RF & Microwave Products
  - Tooling Products
  - Touch Screen Displays
  - Tubing, Molded and Harnessing Products
  - Wire, Cable and Cable Assemblies
  - List all product types...
- O <u>By Industry</u>
  - Aerospace & Defense Products
  - Appliance
  - Automotive
  - Mutomotive
  - Communications
  - Computer & Consumer Electronics
  - Industrial & Commercial
  - Instrumentation & Medical
- O By Brand
- O A to Z
- O <u>Product News</u>

## • **Documentation**

- O Find Documents & Drawings
- O Find CAD Models
- O SPICE/Electrical Models
- O NAFTA Certificate of Origin
- O White Papers

## Resources

- O RoHS Compliance & Alternates
- O Cross Reference Products
- O Compare Multiple Products
- O Check Distributor Inventory
- O Find Authorized Distributors

## • My Account

- O Sign In
- O Register

# • Customer Support

- O Support
- O RoHS Support Center
- O Glossary of Terms
- O eBulletin Newsletter

## **RP730012 Product Details**



RP730012

Active

### Power PC Board Relays



#### **Product Highlights:**

- RPII/1 Series
- Contact Arrangement = 1 Form A, SPST-NO, 1 N/O
- Contact Current Rating = 16 Amps.
- Monostable Coil Magnetic System
- Without Coil Suppression Diode

View all Features | Find Similar Products



- Check Pricing & Availability
- Search for Tooling
- Product Feature Selector
- Compare Products
- Contact Us About This Product

#### **Documentation & Additional Information**

#### **Product Drawings:**

• None Available

#### Catalog Pages/Data Sheets:

• Power PCB Relay RPII/1 (PDF, English)

#### **Product Specifications:**

None Available

#### **Application Specifications:**

None Available

#### Instruction Sheets:

None Available

#### **CAD Files:**

None Available

#### **Additional Information:**

• Product Line Information

#### Related Products:

• <u>Tooling</u>

#### List all Documents

Product Features (Please use the Product Drawing for all design activity)

### **Product Type Features:**

• <u>Termination Type</u> = Through Hole

#### **Electrical Characteristics:**

- Contact Current Rating (Amps.) = 16
- Coil Resistance (?) = 270
- <u>Coil Power, Nominal (mW)</u> = 500
- Actuating System = DC
- <u>Coil Power, Nominal (W)</u> = 0.50
- Input Voltage (VDC) = 12
- Dielectric Strength Coil Contacts (V rms) = 4000
- Tracking Resistance of Relay Base = PTI250

### **Body Related Features:**

- Series = RPII/1
- Polarized = No
- Enclosure Color = Clear

### **Contact Related Features:**

- Mounting Options = PC Board, Socket
- Enclosure = Immersion Cleanable
- FCC Part 68 Isolation = No
- Relay Type = PCB
- Contact Material = Silver Cadmium Oxide
- Approx. Dimensions (L x W x H) (nm[in]) = 29.00 x 12.60 x 25.50 [1.141 x .496 x 1.003]
- Contact Type = Single
- Pin Configuration = Industry Standard 5mm
- Wiring Diagram= 1 Form A

### **Housing Related Features:**

- Pick-Up (V) = 8.4
- Drop-Out (V) = 1.2

## Configuration Related Features:

- Contact Arrangement = 1 Form A, SPST-NO, 1 N/O
- Coil Magnetic System = Monostable
- <u>Coil Suppression Diode</u> = Without
- <u>Coil Selection Criteria</u> = Nominal Voltage
- Coil Latching = Without
- LED Indicator = Without
- Number of Coils = 1

## Industry Standards:

- RoHS/ELV Compliance = RoHS/Not ELV Compliant
- Lead Free Solder Processes = Wave solder capable to 240C, Wave solder capable to 260C
- RoHS/ELV Compliance History = Converted to comply with RoHS not ELV directives

### Packaging Related Features:

Packaging Method = Carton Bar

#### Other

- Electrical Spacing = 8.0mm Clearance 8.0mm Creepage
- Brand = Schrack

- Approved Standards = VDE Component Mark, UL Recognized for Canada and US
- Number of Poles = 1

Provide Website Feedback | Contact Customer Support
Home | Customer Support | Suppliers | Site Map | Privacy Policy | Browser Support
2008 Tyco Electronics Corporation All Rights Reserved