Our commitment. Your advantage.

Search

My Account

Products

Documentation

Resources

My Account

Customer Support

<u>Home</u> > <u>Products</u> > <u>By Type</u> > <u>Resistors</u> > <u>Product Feature Selector</u> > Product Details

404806392015 Product Details



Check Pricing & Availability

Contact Us About This Product

Product Feature Selector

Search for Tooling

Quick Links


Variable Resistors

Converted to EU RoHS/ELV Compliant (Statement of Compliance)

Product Highlights:


- Variable Resistor
- Resistor Type = Trimmer
- Resistance Selection = K?
- Resistance = 500K ?
- Power Rating = .50 W

View all Features




🕒 Add to My Part List 🕡









<u>Active</u>

Documentation & Additional Information

Product Drawings:

None Available

Catalog Pages/Data Sheets:

• <u>Professional Trimmers - Type 4295 Series - Tyco Elec...</u> (PDF, English)

Product Specifications:

None Available

Application Specifications:

• None Available

Instruction Sheets:

None Available

CAD Files:

None Available

Additional Information:

• Product Line Information

Related Products:

• <u>Tooling</u>

<u>List all Documents</u>

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- Product Type = Variable Resistor
- <u>Resistor Type</u> = Trimmer
- Resistance (?) = 500K
- <u>Element</u> = Cermet
- <u>Sealed</u> = Yes
- <u>Mount Angle</u> = Horizontal
- <u>Termination Type</u> = PCB Terminations

Electrical Characteristics:

- Resistance Selection (?) = K
- <u>Power Rating (W)</u> = 0.50
- <u>Tolerance (%)</u> = 10

Termination Related Features:

• <u>Termination Post Orientation</u> = 5.0 x 5.0

Body Related Features:

- <u>Series</u> = 4295
- Package, Component Size = 10

Configuration Related Features:

- <u>Sections</u> = Single
- Adjustment Location = Top
- <u>Adjustment Style</u> = Screwdriver Slot
- Operating Function = Single Turn

Industry Standards:

- RoHS/ELV Compliance = RoHS compliant, ELV compliant
- <u>Lead Free Solder Processes</u> = Wave solder capable to 240?C, Wave solder capable to 260?C, Wave solder capable to 265?C
- RoHS/ELV Compliance History = Converted to comply with RoHS directive

Conditions for Usage:

<u>Temperature Coefficient (ppm/?C)</u> = 100

• Brand = Citec

Provide Website Feedback | Need Help?