

Our commitment. Your advantage.

Search

**Live Product Chat** 

Check Pricing & Availability

Contact Us About This Product

Search for Tooling **Product Feature Selector** 

**Quick Links** 

**Documentation** 


Resources

My Account

**Customer Support** 

<u>Home</u> > <u>Products</u> > <u>By Type</u> > <u>Resistors</u> > <u>Product Feature Selector</u> > <u>Product Details</u>

# 404806505008 Product Details



404806505008

(1623866-8)

TE Internal Number: 1623866-8



#### **Variable Resistors**

Converted to EU RoHS/ELV Compliant (Statement of Compliance)

## **Product Highlights:**

- Variable Resistor
- Resistor Type = Trimmer
- Resistance Selection = K?
- Resistance = 2K?
- Power Rating = .75 W

View all Features









## **Documentation & Additional Information**

## **Product Drawings:**

• PROFESSIONAL TRIMMERS SERIES 433PW (PDF, English)

### Catalog Pages/Data Sheets:

Professional Trimmers - Type 433PW Series - Tyco Ele... (PDF, English)

#### **Product Specifications:**

• None Available

## **Application Specifications:**

None Available

# **Instruction Sheets:**

• None Available

## **CAD Files:**

None Available

# **Additional Information:**

• Product Line Information

#### **Related Products:**

Tooling

## **Product Features** (Please use the Product Drawing for all design activity)

## **Product Type Features:**

- Product Type = Variable Resistor
- <u>Resistor Type</u> = Trimmer
- Resistance (?) = 2K
- <u>Element</u> = Cermet
- <u>Sealed</u> = Yes
- <u>Termination Type</u> = PCB Terminations

# **Electrical Characteristics:**

- Resistance Selection (?) = K
- Power Rating (W) = 0.75
- <u>Tolerance (%)</u> = 10

## **Termination Related Features:**

• <u>Termination Post Orientation</u> = 12.7 x 2.5

## **Body Related Features:**

- <u>Series</u> = 433
- Package, Component Size = 19

## **Configuration Related Features:**

- <u>Sections</u> = Single
- Adjustment Location = Side
- Operating Function = Multi Turn, Rectilinear

# **Industry Standards:**

List all Documents

- RoHS/ELV Compliance = RoHS compliant, ELV compliant
- Lead Free Solder Processes = Wave solder capable to 240?C, Wave solder capable to 260?C, Wave solder capable to 265?C
- RoHS/ELV Compliance History = Converted to comply with RoHS directive

## Conditions for Usage:

• Temperature Coefficient (ppm/?C) = 250

## Other:

• Brand = Citec