

AMP | AMP Auto Squib Products

TE Internal #: 1376030-1


Housing for Female Terminals, Wire-to-Board / Wire-to-Device, 2 Position, .122 in [3.1 mm] Centerline, Yellow, AMP Auto Squib

Products

View on TE.com >



Connectors > Automotive Connectors > Connector Housings



Connector & Housing Type: Housing for Female Terminals

Mating Pin Diameter: 1 mm [.039 in]

Connector System: Wire-to-Board, Wire-to-Device

Number of Positions: 2

Centerline (Pitch): 3.1 mm [.122 in]

Features

Product Type Features

Connector Shape	Rectangular
Connector & Housing Type	Housing for Female Terminals
Connector System	Wire-to-Board, Wire-to-Device
Sealable	No
Hybrid Connector	No
Configuration Features	

Configuration Features

Number of Positions	2	
Number of Rows	1	

Body Features

Cable Exit Angle	90°
Body Material	PBT
Primary Product Color	Yellow

Contact Features

Contact Size	1mm
Contact Type	Socket
Mating Pin Diameter	1 mm[.039 in]

Mechanical Attachment

Mounting Feature Without



Terminal Position Assurance	Yes
Strain Relief	Without
Mating Alignment Type	Polarized
Mating Alignment	With
Connector Mounting Type	Cable Mount (Free-Hanging)
Housing Features	
Centerline (Pitch)	3.1 mm[.122 in]
Dimensions	
Product Width	14.3 mm[.563 in]
Product Length	14 mm[.551 in]
Product Height	29.5 mm[1.161 in]
Usage Conditions	
Operating Temperature (Max)	70 °C, 75 °C, 80 °C[158 °F][167 °F][176 °F]
	70 °C, 75 °C, 80 °C[158 °F][167 °F][176 °F] -30 – 80 °C[-22 – 176 °F]
Operating Temperature (Max)	
Operating Temperature (Max) Operating Temperature Range	
Operating Temperature (Max) Operating Temperature Range Industry Standards	-30 – 80 °C[-22 – 176 °F]
Operating Temperature (Max) Operating Temperature Range Industry Standards UL Flammability Rating	-30 – 80 °C[-22 – 176 °F]
Operating Temperature (Max) Operating Temperature Range Industry Standards UL Flammability Rating Packaging Features	-30 – 80 °C[-22 – 176 °F] UL 94HB
Operating Temperature (Max) Operating Temperature Range Industry Standards UL Flammability Rating Packaging Features Packaging Method	-30 – 80 °C[-22 – 176 °F] UL 94HB

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2022 (224) Candidate List Declared Against: JUNE 2022 (224) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC



Free

Solder Process Capability

Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts





Also in the Series | AMP Auto Squib Products




Automotive Housings(13)



Automotive Terminals(2)



Other Automotive Connector Accessories(8)



PCB Headers & Receptacles(1)

Documents

Product Drawings
SQUIB CONN HSG IIDIA

Japanese

CAD Files

Customer View Model ENG_CVM_1376030-1_C1.3d_igs.zip

English



Customer View Model

ENG_CVM_1376030-1_C1.3d_stp.zip

English

Customer View Model

ENG_CVM_1376030-1_C1.2d_dxf.zip

English

3D PDF

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Product Specifications

SQUIB Connector 11DIA

Japanese

Product Specification

Japanese

SQUIB Connector 11DIA

Japanese

Product Specification

Japanese

Instruction Sheets

Instruction Sheet (non U.S.)

Japanese

Instruction Sheet (non U.S.)

Japanese