SPLICE

TE Internal #: 140792-2

Splices, 13.5 – 9 AWG Wire Size, 2.6 – 6.1 mm² Wire Size, Splice

Capacity 3, 5000 – 13000 CMA Wire Size, Brass, Pigtail Splice

Splice, SPLICE

View on TE.com >



Terminals & Splices > Splices











Wire Size: 5000 – 13000 CMA

Sealable: No

Splice Capacity: 3

Features

Product Type Features

Splice Type Serrated Pigtail Splice No	Sealable	No
Serrated	Splice Type	Pigtail Splice
	Serrated	No
Compatible With Discrete Wire Type Solid, Stranded	Compatible With Discrete Wire Type	Solid, Stranded
Wire Insulation Support Retention Type Non-Insulation Support	Wire Insulation Support Retention Type	Non-Insulation Support

Configuration Features

Strip Orientation	End Feed
Splice Capacity	3
Number of Serrations	0
Compatible With Wire & Cable Type	Discrete Wire

Electrical Characteristics

Operating Voltage	250 V
-------------------	-------

Body Features

Weight per Piece	.429 g
Plating Material	Tin



	D
Primary Product Material	Brass
Contact Features	
Contact Plating Material	Tin
Barrel Type	Open
Mechanical Attachment	
Wire Insulation Support	Without
Dimensions	
Wire Size	5000 – 13000 CMA
Terminal Material Thickness	.64 mm[.025 in]
Overall Product Length	5.72 mm[.225 in]
Usage Conditions	
Insulation Option	Uninsulated
Operating Temperature Range	-40 – 110 °C[-40 – 230 °F]
Operation/Application	
Heavy Duty	No
Compatible With Wire Base Material	Copper
Industry Standards	
Government Qualified Splice	No
Packaging Features	
Packaging Quantity	10000
Packaging Method	Strip

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2022 (224) Candidate List Declared Against: JUNE 2022 (224) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC



Free

Solder Process Capability

Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



TE Part # 42627-4 SPLICE 3232-8282 .0198 NPST



TE Part # 626207-1 SPECIAL SPLICE 20-18 AWG LATAO



TE Part # 160644-3 SPLICE 20-15 AWG .016 TPBR











Also in the Series | SPLICE





Documents



Product Drawings

SPLICE 5000-12000 0.63MM TPBR

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_140792-2_J.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_140792-2_J.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_140792-2_J.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Product Specifications

Application Specification

English