


TE Internal #: 1604038-1 Power Contacts, Contact, 600 VAC, 600 VDC, Silver, 0 AWG Wire Size, 21 – 60 mm<sup>2</sup> Wire Size, 41444 – 118412 CMA Wire Size, Wireto-Wire, Wire & Cable

### View on TE.com >



Connectors > Power Connectors > Power Contacts



Power Contact Type: Contact

Operating Voltage: 600 VDC

Contact Mating Area Plating Material: Silver

Wire Size: **0 AWG** 

# Features

### **Product Type Features**

Power Contact Type	Contact
Connector System	Wire-to-Wire
Connector & Contact Terminates To	Wire & Cable
Electrical Characteristics	
Operating Voltage	600 VDC
Contact Features	
Contact Mating Area Plating Material	Silver
Contact Current Rating (Max)	180 A
Contact Type	Tab
Contact Retention Within Housing	With
Mating Tab Width	12.7 mm[.5 in]
Mating Tab Thickness	6 mm[.236 in]
Contact Base Material	Copper Alloy
Contact Mating Area Plating Material Thickness	1.27 μm[50 μin]
Wire Contact Termination Area Plating Thickness	1.27 μm[50 μin]

# 1604038-1

Power Contacts, Contact, 600 VAC, 600 VDC, Silver, 0 AWG Wire Size, 21 – 60 mm<sup>2</sup> Wire Size, 41444 – 118412 CMA Wire Size, Wire-to-Wire, Wire & Cable



Wire Contact Termination Area Plating Material	Silver
Wire Contact Termination Area Plating Material Finish	Bright
Contact Orientation	Straight
Contact Underplating Material	Nickel
Contact Underplating Material Thickness	50 μm[1.27 μin]
Barrel Type	Closed Barrel
Termination Features	
Termination Method to Wire & Cable	Crimp
Mechanical Attachment	
Connector Mounting Type	Cable Mount (Free-Hanging)
Dimensions	
Wire Size	41444 – 118412 CMA
Usage Conditions	
Operating Temperature Range	-40 - 105 °C[-40 - 221 °F]
Operation/Application	
Circuit Application	Power
Industry Standards	
Agency/Standard	UL
UL Rating	Recognized
UL Flammability Rating	UL 94V-0
UL File Number	E28476
Packaging Features	
Packaging Method	Box
Packaging Quantity	400
Other	
Wire/Cable Type	Discrete Wire
Wire Type	Stranded
Product Compliance For compliance documentation, visit the product page on TE.com>	
EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant

**C** For support call+1 800 522 6752

# 1604038-1

Power Contacts, Contact, 600 VAC, 600 VDC, Silver, 0 AWG Wire Size, 21 – 60 mm<sup>2</sup> Wire Size, 41444 – 118412 CMA Wire Size, Wire-to-Wire, Wire & Cable



China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2022 (224) Candidate List Declared Against: JUNE 2022 (224) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free

Solder Process Capability

Not applicable for solder process capability

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

# **Compatible Parts**



# Documents

# Product Drawings CONTACT,175A/180A,1/0 AWG,L/P

English

### CAD Files

**Customer View Model** 

ENG\_CVM\_CVM\_1604038-1\_A.2d\_dxf.zip

English

### 3D PDF

3D

# 1604038-1

Power Contacts, Contact, 600 VAC, 600 VDC, Silver, 0 AWG Wire Size, 21 – 60 mm<sup>2</sup> Wire Size, 41444 – 118412 CMA Wire Size, Wire-to-Wire, Wire & Cable



Customer View Model

ENG\_CVM\_CVM\_1604038-1\_A.3d\_igs.zip

English

Customer View Model

ENG\_CVM\_CVM\_1604038-1\_A.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

POWER\_CONNECTORS\_CATALOG\_SEC02\_CABLE\_MOUNTED

English

2\_PIECE\_POWER\_CONNECTORS\_qrg\_4-1773458-1

English

**Product Specifications** 

Application Specification

English

Agency Approvals Agency Approval Document

English