MW3-12A V ACTIVE

CII | CII MW

TE Internal #: 1617096-1 High Frequency Relays, 2 Form C, DPDT, 2 C/O, 12 VDC Input, 1 A, 12 VDC Coil Voltage, 390 Ω Coil Resistance, 369 mW Coil Power (DC), CII MW

View on TE.com >

Relays, Contactors & Switches > Relays > Mil-Aero Relays > High Frequency Relays



High Frequency Relay Contact Arrangement: 2 Form C, DPDT, 2 C/O
High Frequency Relay Input Voltage: 12 VDC
High Frequency Relay Contact Current Rating: 1 A
High Frequency Relay Coil Voltage Rating: 12 VDC
High Frequency Relay Coil Resistance: 390 Ω

Features

Product Type Features

Enclosure Type	Hermetically Sealed
Coil Latching	Without
Relay Type	Military/Aerospace High Performance
Product Type	Relay
MOSFET Driver	Without
Configuration Features	
Transistor Driver	Without
Electrical Characteristics	
Coil Magnetic System	Non-Polarized, Monostable
Vibration	10G's, 10 – 500Hz
Actuating System	DC
Shock	30G's, 6ms
Coil Suppression Diode	Without
Coil Power Measurement	Milliwatts
Coil Polarity Protection Diode	Without
High Frequency Relay Input Voltage	12 VDC
High Frequency Relay Coil Voltage Rating	12 VDC



MW3-12A

High Frequency Relays, 2 Form C, DPDT, 2 C/O, 12 VDC Input, 1 A, 12 VDC Coil Voltage, 390 Ω Coil Resistance, 369 mW Coil Power (DC), CII MW



High Frequency Relay Coil Resistance	390 Ω
High Frequency Relay Coil Power Rating (DC)	369 mW
Contact Features	
High Frequency Relay Contact Arrangement	2 Form C, DPDT, 2 C/O
High Frequency Relay Contact Current Rating	1 A
Termination Features	
Termination Type	Long Leads
Mechanical Attachment	
High Frequency Relay Mounting Type	Printed Circuit Board
Usage Conditions	
Operating Temperature Range	-55 – 85 °C
Product Compliance	
For compliance documentation, visit the product page on TE.com>	
EU RoHS Directive 2011/65/EU	Not Compliant

EU ELV Directive 2000/53/EC

China RoHS 2 Directive MIIT Order No 32, 2016

EU REACH Regulation (EC) No. 1907/2006

Not Compliant

Restricted Materials Above Threshold

Current ECHA Candidate List: JUNE 2022 (224)Candidate List Declared Against: JAN 2022 (223) SVHC > Threshold: Not Yet Reviewed

Halogen Content

Not Yet Reviewed for halogen content

Solder Process Capability

Not lead free process capable

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked.Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulations, TE's information on SVHC in articles for this part number is still based on the European Chemical Agency (ECHA) 'Guidance on requirements for substances in articles' (Version: 2, April 2011), applying the 0.1% weight on weight concentration threshold at the finished product level. TE is aware of the European Court of Justice ruling of September 10th, 2015 also known as O5A (Once An Article Always An Article) stating that, in case of 'complex object', the threshold for a SVHC must be applied to both the

MW3-12A

High Frequency Relays, 2 Form C, DPDT, 2 C/O, 12 VDC Input, 1 A, 12 VDC Coil Voltage, 390 Ω Coil Resistance, 369 mW Coil Power (DC), CII MW



product as a whole and simultaneously to each of the articles forming part of its composition. TE has evaluated this ruling based on the new ECHA "Guidance on requirements for substances in articles" (June 2017, version 4.0) and will be updating its statements accordingly.

Compatible Parts



Also in the Series | CII MW



Documents

CAD Files

3D PDF

3D

Customer View Model ENG_CVM_CVM_1617096-1_O.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_1617096-1_O.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1617096-1_O.3d_stp.zip

English

By downloading the CAD file I accept and agree to the Terms and Conditions of use.

Datasheets & Catalog Pages 5-1773450-5_sec2_MW3

English

RELAY

English

MW3-12A

High Frequency Relays, 2 Form C, DPDT, 2 C/O, 12 VDC Input, 1 A, 12 VDC Coil Voltage, 390 Ω Coil Resistance, 369 mW Coil Power (DC), CII MW

