

CII | CII J1MAT Relay

TE Internal #: 1617162-9

TO-5/.100 Grid Relays, 1 Form C, SPDT, 1 C/O, 26 VDC Input, Coil Suppression Diode, Transistor Driver, 1 A, 26 VDC Coil Voltage, CII

J1MAT Relay

View on TE.com >



Relays, Contactors & Switches > Relays > Mil-Aero Relays > TO-5/.100 Grid Relays



TO-5/.100 Grid Relay Contact Arrangement: 1 Form C, SPDT, 1 C/O

TO-5/.100 Grid Relay Input Voltage: 26 VDC

Coil Suppression Diode: With MOSFET Driver: Without Transistor Driver: With

Features

Product Type Features

Enclosure Type	Hermetically Sealed
Relay Type	Military/Aerospace High Performance
Coil Latching	Without
Product Type	Relay
MOSFET Driver	Without

Configuration Features

Transistor Driver	With	
-------------------	------	--

Electrical Characteristics

Coil Magnetic System	Non-Polarized, Monostable
Vibration	30G's, 10 – 3000Hz
Actuating System	DC
Shock	75G's, 6ms
Coil Power Measurement	Milliwatts
TO-5/.100 Grid Relay Input Voltage	26 VDC
Coil Suppression Diode	With
Coil Voltage	26 VDC
TO-5/.100 Grid Relay Coil Resistance	2000 Ω



TO-5/.100 Grid Relay Coil Power Rating (DC)	351 mW
Coil Polarity Protection Diode	With
TO-5/.100 Grid Relay Contact Switching Voltage (Max)	28
Contact Features	
Contact Current Class	Low Level – 1 A
Pin Configuration	.200" x .300" Spreader Pad
TO-5/.100 Grid Relay Contact Arrangement	1 Form C, SPDT, 1 C/O
TO-5/.100 Grid Relay Contact Current Rating	1 A
Termination Features	
Termination Type	PC Pins
Mechanical Attachment	

Printed Circuit Board

-65 – 125 °C

Product Compliance

Usage Conditions

For compliance documentation, visit the product page on TE.com>

TO-5/.100 Grid Relay Mounting Type

Operating Temperature Range

EU RoHS Directive 2011/65/EU	Not Compliant
EU ELV Directive 2000/53/EC	Not Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2022 (224) Candidate List Declared Against: JAN 2022 (223) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not lead free process capable

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits

TO-5/.100 Grid Relays, 1 Form C, SPDT, 1 C/O, 26 VDC Input, Coil Suppression Diode, Transistor Driver, 1 A, 26 VDC Coil Voltage, CII J1MAT Relay



as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



Also in the Series | CII J1MAT Relay



Documents

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_1617162-9_O.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_1617162-9_O.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1617162-9_O.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

RELAY

English