

Sigma | Sigma SC

TE Internal #: 1624055-2

High Frequency & RF Inductors, Radio Frequency, Through Hole - Solder, Ammo Packed, 7 x 2.8 mm, 10 %, Inductance .82 μ H, 455

mA, Sigma SC

View on TE.com >



Passive Components > Inductors > High Frequency & RF Inductors



Inductor Type: Radio Frequency

Termination Method to Printed Circuit Board: Through Hole - Solder

Packaging Method: Ammo Packed

Passive Component Dimensions: 7 x 2.8 mm

Passive Component Tolerance: 10 %

Features

Product Type Features

Troduct Type realures	
Inductor Type	Radio Frequency
Element Type	Wire Wound
Package Size Code	SC30
Electrical Characteristics	
Self Resonant Frequency	.25 GHz
Passive Component Tolerance	10 %
Inductance	.82 μΗ
Current Rating (Max)	455 mA
DC Resistance	.85 Ω
Body Features	
Passive Component Lead Type	Axial-Leaded
Termination Features	
Termination Method to Printed Circuit Board	Through Hole - Solder
Dimensions	
Passive Component Dimensions	7 x 2.8 mm
Usage Conditions	

-55 – 100 °C

Operating Temperature Range



Packaging Features

Packaging Method	Ammo Packed
Other	
Inductor Quality Factor	28

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Not Yet Reviewed
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2022 (224) Candidate List Declared Against: JUNE 2022 (224) Does not contain REACH SVHC
Halogen Content	Not Yet Reviewed for halogen content
Solder Process Capability	Wave solder capable to 265°C

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts














Also in the Series | Sigma SC







Documents

Product Drawings

SC30-10-2512-10 0.82UH AMMO 1000

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_1624055-2_BA.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_1624055-2_BA.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1624055-2_BA.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

1309350_PASSIVE_COMPONENT

English

Axial Leaded Power Inductors - Type SC10, SC15, SC30 Series - Tyco Electronics Passives

English