#### **AMP POWER TAP**


TE Internal #: 167892-3

Power Terminals, Power Tap, Terminates To Printed Circuit Board, 8 Position, 2.54 mm [.1 in] Centerline, Power, Uninsulated, Vertical

View on TE.com >



Terminals & Splices > Power Terminals











Power Terminal Type: Power Tap

Product Terminates To: Printed Circuit Board

Contact Mating Area Plating Material Finish

Contact Underplating Material

Contact Current Rating (Max)

Contact Mating Area Plating Material

Contact Fabrication

Number of Positions: 8

Contact Current Rating (Max): 40 A
Centerline (Pitch): 2.54 mm [.1 in]

### **Features**

### Product Type Features

Terminal Style	Tab
Power Terminal Type	Power Tap
Configuration Features	
Number of Positions	8
PCB Mount Orientation	Vertical
Body Features	
Terminal Profile	Standard
Contact Features	
PCB Contact Termination Area Plating Material Finish	Bright

Bright

Nickel

40 A

Tin

Stamped & Formed



Contact Mating Area Plating Material Thickness	5 μm[196.85 μin]
PCB Contact Termination Area Plating Material	Tin
PCB Contact Termination Area Plating Material Thickness	5 μm[196.85 μin]
Wire Contact Termination Area Plating Material	Nickel
Contact Base Material	Phosphor Bronze
Termination Features	
Termination Method to Printed Circuit Board	Through Hole - Press-Fit
Product Terminates To	Printed Circuit Board
Mechanical Attachment	
Contact Mating Retention Type	Dimple
Housing Features	
Centerline (Pitch)	2.54 mm[.1 in]
Dimensions	
PCB Thickness (Recommended)	3.18 mm[.125 in]
Overall Product Length	13 mm[.511 in]
Mating Area Interface Dimensions	6.35 x .81 mm[.25 x .32 in]
Usage Conditions	
Insulation Option	Uninsulated
Operating Temperature Range	-55 – 85 °C[-67 – 185 °F]
Operation/Application	
Circuit Application	Power
Packaging Features	
Packaging Method	Box

# **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2022 (224) Candidate List Declared Against: JUNE 2022 (224)



Does not contain REACH SVHC

Halogen Content

Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC

Free

Solder Process Capability

Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

# Compatible Parts



#### **Documents**

**Product Drawings** 

8 POS LINKING TERM W ACT. PIN

English

**CAD Files** 

**Customer View Model** 

ENG\_CVM\_CVM\_167892-3\_E.2d\_dxf.zip

English

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_167892-3\_E.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_167892-3\_E.3d\_stp.zip

English

Power Terminals, Power Tap, Terminates To Printed Circuit Board, 8 Position, 2.54 mm [.1 in] Centerline, Power, Uninsulated, Vertical



By downloading the CAD file I accept and agree to the **Terms and Conditions** of use

## Datasheets & Catalog Pages

POWER\_CONNECTORS\_CATALOG\_SEC02\_CABLE\_MOUNTED

English

# **Product Specifications**

**Application Specification** 

English

## **Agency Approvals**

**UL Report** 

English