172236-2 - ACTIVE

Positive Lock | Positive Lock 312

TE Internal #: 172236-2 Crimp Terminal Housings, Receptacle, Receptacle, 3 Position, Straight, UL 94V-2, Black, Nylon, Contact Mating Retention, Positive Lock 312

View on TE.com >

Terminals & Splices > Terminal Housings, Insulation Sleeves & Blocks > Crimp Terminal Housings



Terminal Type: Receptacle Housing Type: Receptacle Number of Positions: 3 Terminal Orientation: Straight UL Flammability Rating: UL 94V-2

Features



Product Type Features

Terminates To	Wire & Cable			
Product Type	Terminal Housing			
Sealable	No			
Connector System	Wire-to-Board, Wire-to-Wire			
Housing Type	Receptacle			
Insulated	No			
Configuration Features				
Number of Positions	3			
Body Features				
Primary Product Color	Black			
Contact Features				
Terminal Type	Receptacle			
Terminal Orientation	Straight			
Contact Mating Retention	With			

C For support call+1 800 522 6752

172236-2

Crimp Terminal Housings, Receptacle, Receptacle, 3 Position, Straight, UL 94V-2, Black, Nylon, Contact Mating Retention, Positive Lock 312



Mechanical Attachment

Mating Alignment Type	Polarization
Mating Alignment	With
Crimp Terminal Housing Mounting Style	Cable Mount (Free-Hanging)
Housing Features	
Housing Material	Nylon
Centerline (Pitch)	8.32 mm[.327 in]
Usage Conditions	
Operating Temperature Range	-40 – 105 °C[-40 – 221 °F]
Industry Standards	
UL Flammability Rating	UL 94V-2
Packaging Features	
Packaging Quantity	100

Product Compliance

For compliance documentation, visit the product page on TE.com>

DallC	Diroctivo	2011	

Compliant

Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free	
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2022 (224) Candidate List Declared Against: JUNE 2022 (224) Does not contain REACH SVHC	
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold	
EU ELV Directive 2000/53/EC	Compliant	
EU ROHS DIrective 2011/05/EU	Compliant	

Solder Process Capability

Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides

172236-2

Crimp Terminal Housings, Receptacle, Receptacle, 3 Position, Straight, UL 94V-2, Black, Nylon, Contact Mating Retention, Positive Lock 312



on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts





Also in the Series | Positive Lock 312



		and the second second
Crimp Terminal Housings(4)	Insertion & Extraction Tools(1)	Quick Disconnects(7)

Documents

Product Drawings POSITIVE LOCK 312 HOUSING

English

CAD Files

3D PDF

3D

Customer View Model ENG_CVM_CVM_172236-2_F.2d_dxf.zip

English

Customer View Model

& For support call+1 800 522 6752

172236-2

Crimp Terminal Housings, Receptacle, Receptacle, 3 Position, Straight, UL 94V-2, Black, Nylon, Contact Mating Retention, Positive Lock 312



ENG_CVM_CVM_172236-2_F.3d_igs.zip

English

Customer View Model ENG_CVM_CVM_172236-2_F.3d_stp.zip

English

By downloading the CAD file I accept and agree to the Terms and Conditions of use.

Product Specifications

Product Specification

English

3-Position, Sealed Beam Connector

Japanese

Product Specification

English

JAPANESEE

English

Product Environmental Compliance Product Compliance

English

Product Compliance

English