

### **AMP-IN**

TE Internal #: 172890-2

Housing, Plug, Wire-to-Board, 2 Position, 2 mm [.079 in] Centerline,

Crimp, 1 Row, Natural, Printed Circuit Board, Power & Signal

View on TE.com >



Connectors > PCB Connectors > Wire-to-Board Connectors > Wire-to-Board Connector Assemblies & Housings











Connector Product Type: Housing
Connector & Housing Type: Plug
Connector System: Wire-to-Board

Number of Positions: 2

Centerline (Pitch): 2 mm [ .079 in ]

### **Features**

# Product Type Features

Connector Product Type	Housing
Connector & Housing Type	Plug
Connector System	Wire-to-Board
Sealable	No
Connector & Contact Terminates To	Printed Circuit Board
Configuration Features	
Number of Positions	2
Number of Rows	1
Electrical Characteristics	
Operating Voltage	250 VAC
Contact Features	

Inline

Pin

Brass

Contact Layout

Contact Type

Contact Base Material



### **Termination Features**

Termination Method to Wire & Cable	Crimp
Mechanical Attachment	
Strain Relief	Without
Panel Mount Feature	Without
PCB Mount Retention	Without
Mating Retention	Without
Connector Mounting Type	Cable Mount (Free-Hanging)
Housing Features	
Housing Entry Configuration	Both Ends Closed
Housing Material	Nylon 66
Centerline (Pitch)	2 mm[.079 in]
Housing Color	Natural
Dimensions	
Connector Length	4.8 mm[.18 in]
	.14 in
	.17 111
PCB Thickness (Recommended)	1.19 – 1.6 mm, 1.57 mm
PCB Thickness (Recommended) Wire Size	
	1.19 – 1.6 mm, 1.57 mm
Wire Size	1.19 – 1.6 mm, 1.57 mm
Wire Size  Usage Conditions	1.19 – 1.6 mm, 1.57 mm .05 – .15 mm², .12 – .35 mm²
Wire Size  Usage Conditions  Operating Temperature Range	1.19 – 1.6 mm, 1.57 mm .05 – .15 mm², .12 – .35 mm²
Wire Size  Usage Conditions  Operating Temperature Range  Operation/Application	1.19 – 1.6 mm, 1.57 mm .05 – .15 mm², .12 – .35 mm² -40 – 105 °C[-40 – 221 °F]
Wire Size  Usage Conditions  Operating Temperature Range  Operation/Application  Circuit Application	1.19 – 1.6 mm, 1.57 mm .05 – .15 mm², .12 – .35 mm² -40 – 105 °C[-40 – 221 °F]
Wire Size  Usage Conditions  Operating Temperature Range  Operation/Application  Circuit Application  Industry Standards	1.19 – 1.6 mm, 1.57 mm  .05 – .15 mm², .12 – .35 mm²  -40 – 105 °C[-40 – 221 °F]  Power & Signal
Wire Size  Usage Conditions  Operating Temperature Range  Operation/Application  Circuit Application  Industry Standards  UL Flammability Rating	1.19 – 1.6 mm, 1.57 mm  .05 – .15 mm², .12 – .35 mm²  -40 – 105 °C[-40 – 221 °F]  Power & Signal

# **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant



China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2022 (224) Candidate List Declared Against: JUNE 2022 (224) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

# Compatible Parts















### **Documents**

Product Drawings
2P 2MM MINI AMP-IN HDR HSG



English

**CAD Files** 

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_172890-2\_H.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_172890-2\_H.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_172890-2\_H.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

### Datasheets & Catalog Pages

PRINTED CIRCUIT BOARD TERMINALS AND DISCONNECTS

English

### **Product Specifications**

**Product Specification** 

English

### **Product Environmental Compliance**

**TE Material Declaration** 

English

## Agency Approvals

**UL Report** 

English