
179631-1 - ACTIVE

TE Internal #: 179631-1 Housing for Female Terminals, Wire-to-Wire, 16 Position, .086 in [2.2 mm] Centerline, Natural, Signal, Panel Mount, -40 – 85 °C [-40 – 185 °F]

View on TE.com >

Connectors > Automotive Connectors > Connector Housings



Connector & Housing Type: Housing for Female Terminals

Mating Tab Width: 1.5 mm [.059 in]

Connector System: Wire-to-Wire

Number of Positions: 16

Centerline (Pitch): 2.2 mm [.086 in]

Features

Product Type Features



Connector Shape	Rectangular
Connector & Housing Type	Housing for Female Terminals
Connector System	Wire-to-Wire
Sealable	No
Hybrid Connector	No
Configuration Features	
Number of Positions	16
Number of Rows	2
Body Features	
Cable Exit Angle	180°
Body Material	PBT
Primary Product Color	Natural
Contact Features	
Contact Size	1.5mm

179631-1

Housing for Female Terminals, Wire-to-Wire, 16 Position, .086 in [2.2 mm] Centerline, Natural, Signal, Panel Mount, -40 – 85 °C [-40 – 185 °F]



Contact Type	Receptacle
Mating Tab Width	1.5 mm[.059 in]
Mechanical Attachment	
Mounting Feature	Without
Terminal Position Assurance	No
Strain Relief	Without
Mating Alignment Type	Polarized
Mating Alignment	With
Connector Mounting Type	Panel Mount
Housing Features	
Centerline (Pitch)	2.2 mm[.086 in]
Dimensions	
Product Width	21.2 mm[.834 in]
Product Length	49.2 mm[1.93 in]
Product Height	26.2 mm[1.03 in]
Row-to-Row Spacing	8.6 mm[.339 in]

Usage Conditions

Operating Temperature (Max)	70 °C, 75 °C, 80 °C, 85 °C[158 °F][167 °F] [176 °F][185 °F]
Operating Temperature Range	-40 – 85 °C[-40 – 185 °F]
Operation/Application	
Circuit Application	Signal
Packaging Features	
Packaging Quantity	50
Packaging Method	Bag
Other	
Connector Position Assurance Capable	No
Product Compliance For compliance documentation, visit the product page on TE.com>	
EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
	11/01/2022 05

C For support call+1 800 522 6752

179631-1

Housing for Female Terminals, Wire-to-Wire, 16 Position, .086 in [2.2 mm] Centerline, Natural, Signal, Panel Mount, -40 – 85 °C [-40 – 185 °F]



China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2022 (224) Candidate List Declared Against: JUNE 2022 (224) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



Documents

Product Drawings DIAGNOSTIC PLUG HSG 16P NARU.

Japanese

CAD Files

Customer View Model

ENG_CVM_CVM_179631-1_N.2d_dxf.zip

English

3D PDF

3D

Customer View Model

& For support call+1 800 522 6752

179631-1

Housing for Female Terminals, Wire-to-Wire, 16 Position, .086 in [2.2 mm] Centerline, Natural, Signal, Panel Mount, -40 – 85 °C [-40 – 185 °F]



ENG_CVM_CVM_179631-1_N.3d_igs.zip

English

Customer View Model ENG_CVM_CVM_179631-1_N.3d_stp.zip

English

By downloading the CAD file I accept and agree to the Terms and Conditions of use.

Product Specifications Application Specification

English

Instruction Sheets Instruction Sheet (U.S.)

English

Automotive On-Board Diagnostic Connector 179631-1

English