FASTIN-FASTON | FASTIN-FASTON 250

TE Internal #: 180901

Crimp Terminal Housings, Tab, Tab Housing, 4 Position, Straight, Natural, Polyamide, Contact Mating Retention, Mating Alignment,

FASTIN-FASTON 250


View on TE.com >



Terminals & Splices > Terminal Housings, Insulation Sleeves & Blocks > Crimp Terminal Housings











Terminal Type: Tab

Housing Type: **Tab Housing**Number of Positions: **4**Terminal Orientation: **Straight**Primary Product Color: **Natural**

Features

Product Type Features

Terminates To	Wire & Cable
Product Type	Terminal Housing
Sealable	No
Housing Type	Tab Housing
Insulated	No
Configuration Features	
Number of Positions	4
Body Features	
Primary Product Color	Natural
Contact Features	
Terminal Type	Tab
Terminal Orientation	Straight
Contact Mating Retention	With



Mechanical Attachment

Mating Alignment	With
Crimp Terminal Housing Mounting Style	Cable Mount (Free-Hanging)
Housing Features	
Housing Material	Polyamide
Centerline (Pitch)	10.8 mm[.425 in]
Dimensions	
Length	31.5 mm[1.24 in]
Usage Conditions	
Operating Temperature Range	-40 – 105 °C[-40 – 221 °F]
Packaging Features	
Packaging Quantity	1800

Carton

Product Compliance

Packaging Method

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2022 (224) Candidate List Declared Against: JUNE 2022 (224) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on



requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-onreach

Compatible Parts










LATCH

FF 250 TAB 14-12AWG PTBR WITHOUT LATCH





TE Part # 170341-1 FF 250 TAB 14-12AWG BR WITHOUT LATCH



TE Part # 170349-1 FF 250 TAB 22-20AWG BR WITHOUT LATCH



TE Part # 626057-1 FASTIN-ON .110 HOUSING TAB NYLON 6/6











Also in the Series | FASTIN-FASTON 250









Documents

Product Drawings FF 250 TAB HSG 4P NYLON NAT

English



CAD Files

Customer View Model

ENG_CVM_CVM_180901_AW.2d_dxf.zip

English

3D PDF

3D

Customer View Model

ENG_CVM_CVM_180901_AW.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_180901_AW.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

FASTIN_FASTON_Product_Line

English

White Paper: Nylon Discoloration

English

Product Specifications

Application Specification

English

Product Environmental Compliance

MD_180901_122720171230_dmtec

English

MD_180901_122720171230_dmtec

English

Agency Approvals

UL Report

English

UL Report

English