

Alcoswitch

TE Internal #: 1-1437597-1


Keylock Switches, Single Pole - Single Throw Configuration (Pole-Throw), Zinc Alloy, Remove Key Position 1, Hand Soldering Type

View on TE.com >



Relays, Contactors & Switches > Switches > Keylock Switches











Configuration (Pole-Throw): Single Pole - Single Throw

Cylinder Material: Zinc Alloy
Remove Key: Position 1
Soldering Type: Hand

Operating Function: Position 1 Off, Position 2 (On)

Features

Product Type Features

Product Type	Switch
Switch Type	Key Lock
Actuator Style	Key
Illuminated	No
Frame Material	Brushed Chrome

Configuration Features

Configuration (Pole-Throw)	Single Pole - Single Throw
Operating Function	Position 1 Off, Position 2 (On)
Panel Cutout Size	19.3 x 16.3 mm[.76 x .64 in]
Number of Keylock Switch Positions	2

Electrical Characteristics

Contact Resistance	50 mΩ
Keylock Switch Voltage Rating	110 VAC, 120 VAC

Body Features



Actuator Travel	90°
Key Changes	10 Standard
Contact Features	
Contact Timing	Non-Shorting
Terminals/Fixed Contact Type	Screw Type
Keylock Switch Contact Current Rating	1 A
Contact Finish	Silver
Mechanical Attachment	
Lock Body	Zinc Alloy
Keylock Switch Mounting Type	Panel
Housing Features	
Cylinder Material	Zinc Alloy
Remove Key	Position 1
Usage Conditions	
Oil-Tight	No
Operating Temperature (Max)	85 °C
Other	
Life Expectancy	10000 Cycles
Comment	Supplied with 2 brass keys.

Product Compliance

Soldering Type

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant with Exemptions
EU ELV Directive 2000/53/EC	Compliant with Exemptions
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2022 (224) Candidate List Declared Against: JAN 2021 (211) SVHC > Threshold: Pb (1.5% in component) Article Safe Usage Statements: Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per

Hand



homogenous material. Also BFR/CFR/PVC Free

Solder Process Capability

Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



Documents

CAD Files

Customer View Model

ENG_CVM_CVM_1-1437597-1_99.2d_dxf.zip

English

3D PDF

3D

Customer View Model

ENG_CVM_CVM_1-1437597-1_99.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1-1437597-1_99.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use

Datasheets & Catalog Pages

SWITCHES_CORE_PROGRAM_CATALOG

English

2SKF231AEL01

Keylock Switches, Single Pole - Single Throw Configuration (Pole-Throw), Zinc Alloy, Remove Key Position 1, Hand Soldering Type

