1-1825138-6 - ACTIVE

Alcoswitch | Alcoswitch Gemini A

TE Internal #: 1-1825138-6 Toggle Switches, Double Pole - Double Throw Configuration (Pole-Throw), 1/4-40, Sealed, Copper, Gold, Process Sealed, Alcoswitch Gemini A

View on TE.com >

Relays, Contactors & Switches > Switches > Toggle Switches



Configuration (Pole-Throw): Double Pole - Double Throw

Bushing Thread Size: 1/4-40

Sealed Device: Yes

Contact Base Material: Copper

Switch Contact Plating Material: Gold

Features

Product Type Features

Product Type	Switch
Sealed Device	Yes
Toggle Style	Baton Long



Toggle Switch Type	Toggle
Toggle Actuation	Vertical
Configuration Features	
Configuration (Pole-Throw)	Double Pole - Double Throw
Operating Function	On On
Electrical Characteristics	
Dielectric Strength	1000 VAC
Insulation Resistance	1000 MΩ
Contact Resistance	10 mΩ
Toggle Switch Voltage Rating	20 VDC
Body Features	
Actuator Finish	Nickel
Bushing Thread Size	1/4-40
Toggle Switch Seal Type	Environmental
Bushing Style	Threaded

1-1825138-6

Toggle Switches, Double Pole - Double Throw Configuration (Pole-Throw), 1/4-40, Sealed, Copper, Gold, Process Sealed, Alcoswitch Gemini A



Contact Features

Contact Base Material	Copper
Switch Contact Plating Material	Gold
Toggle Switch Contact Current Rating	.4 A
Termination Features	
Termination Type	Wire Lugs
Mechanical Attachment	
Toggle Switch Mounting Type	Solder
Housing Features	
Process Sealed	Yes
Dimensions	
Toggle Length	10.4 mm[.41 in]
	.37 in
Industry Standards	
UL Flammability Rating	UL 94V-0

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant with Exemptions
EU ELV Directive 2000/53/EC	Compliant with Exemptions
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2022 (224) Candidate List Declared Against: JUL 2021 (219) SVHC > Threshold: Pb (4% in Component Part) Aticle Safe Usage Statements: Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Wave solder capable to 265°C
Product Compliance Disclaimer	

1-1825138-6

Toggle Switches, Double Pole - Double Throw Configuration (Pole-Throw), 1/4-40, Sealed, Copper, Gold, Process Sealed, Alcoswitch Gemini A



This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach


Compatible Parts





TE Part # 4-1825136-3 A101SYAQ04

Also in the Series | Alcoswitch Gemini A



Documents

Product Drawings A201SCWZB04

English

Datasheets & Catalog Pages

C For support call+1 800 522 6752

1-1825138-6

Toggle Switches, Double Pole - Double Throw Configuration (Pole-Throw), 1/4-40, Sealed, Copper, Gold, Process Sealed, Alcoswitch Gemini A



SWITCHES_CORE_PROGRAM_CATALOG

English

GEMINI_SERIES_SWITCHES_QUICK_REF_GUIDE_2-1773458-5

English