206794-4 - ACTIVE


AMPLIMITE

TE Internal #: 206794-4 D-Sub Connector Contacts, Pin, Size 20, Copper Alloy, Gold, Crimp, 28 – 26 AWG Wire Size, .08 – .15 mm² Wire Size, Wire & Cable, 7.5 A, Signal

View on TE.com >



Connectors > D-Shaped Connectors > D-Sub Connector Contacts



Contact Type: Pin D-Sub Contact Size: 20 Contact Base Material: Copper Alloy Contact Mating Area Plating Material: Gold Termination Method to Wire & Cable: Crimp

Features

Product Type Features

Product Type

Connector & Contact Terminates To

Contact

Wire & Cable

Body Features

Color Code	Yes
Contact Features	
Pin Diameter	.04 mm
Contact Color Bands	Black, Red
	50 µin
Contact Style	Long
Contact Underplating Material	Copper
Contact Type	Pin
D-Sub Contact Size	20
Contact Base Material	Copper Alloy
Contact Mating Area Plating Material	Gold
Contact Current Rating (Max)	7.5 A
Termination Features	
Termination Post Length	.33 mm
Termination Method to Wire & Cable	Crimp

206794-4

D-Sub Connector Contacts, Pin, Size 20, Copper Alloy, Gold, Crimp, 28 – 26 AWG Wire Size, .08 – .15 mm² Wire Size, Wire & Cable, 7.5 A, Signal



Dimensions

Insulation Diameter (Max)	.07 mm[1.83 in]
Post Diameter	.07 mm[1.73 in]
Wire Size	.08 – .15 mm²
Usage Conditions	
Operating Temperature Range	-55 – 125 °C[-67 – 257 °F]
Operation/Application	
High Current	No
Circuit Application	Signal
Packaging Features	
Packaging Quantity	1000
Packaging Method	Package
Other	
Comment	Contact is color coded.

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant with Exemptions
EU ELV Directive 2000/53/EC	Compliant with Exemptions
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2022 (224) Candidate List Declared Against: JAN 2022 (223) SVHC > Threshold: Pb (1.2% in Component Part) Article Safe Usage Statements: Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability
Product Compliance Disclaimer	

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these

206794-4

D-Sub Connector Contacts, Pin, Size 20, Copper Alloy, Gold, Crimp, 28 – 26 AWG Wire Size, .08 – .15 mm² Wire Size, Wire & Cable, 7.5 A, Signal



limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-onreach

Compatible Parts



Documents

Product Drawings PIN CONTACT, SZ 20

English

CAD Files 3D PDF

3D

Customer View Model

ENG_CVM_CVM_206794-4_N.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_206794-4_N.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_206794-4_N.3d_stp.zip

English

By downloading the CAD file I accept and agree to the Terms and Conditions of use

Product Specifications Application Specification

English

Instruction Sheets Instruction Sheet (U.S.) English