

METRIMATE

TE Internal #: 207444-9

PCB Mount Header, Vertical, Wire-to-Board, 18 Position, 5 mm [. 197 in] Centerline, Fully Shrouded, Tin, Through Hole - Solder,


Power & Signal, Black


View on TE.com >




Connectors > PCB Connectors > PCB Headers & Receptacles











Connector System: Wire-to-Board

Number of Positions: 18

Number of Rows: 6

Centerline (Pitch): 5 mm [.197 in]
PCB Mount Orientation: Vertical

Features

Product Type Features

Connector System	Wire-to-Board
Header Type	Fully Shrouded
Sealable	No
Connector & Contact Terminates To	Printed Circuit Board
PCB Connector Assembly Type	PCB Mount Header
Configuration Features	
Number of Columns	3
Number of Loaded Positions	18
Connector Contact Load Condition	Fully Loaded
Number of Positions	18
Number of Rows	6
PCB Mount Orientation	Vertical
Electrical Characteristics	

600 VAC

Operating Voltage



Body Features

Primary Product Color	Black
Contact Features	
Contact Layout	Matrix
PCB Contact Termination Area Plating Material Thickness	3.81 μm[150 μin]
Mating Pin Diameter	1.75 mm[.069 in]
Contact Underplating Material Thickness	1.27 μm[50 μin]
Contact Mating Area Plating Material Thickness	3.81 μm[150 μin]
PCB Contact Termination Area Plating Material Finish	Matte
Contact Mating Area Plating Material Finish	Matte
Contact Underplating Material	Nickel
PCB Contact Termination Area Plating Material	Tin
Contact Mating Area Plating Material	Tin
Contact Type	Pin
Contact Current Rating (Max)	7.5 A
Termination Features	
Round Termination Post & Tail Diameter	.99 mm[.039 in]
Termination Method to Printed Circuit Board	Through Hole - Solder
Mechanical Attachment	
Mating Alignment Type	Polarization
Mating Retention	With
PCB Mount Retention Type	Screw Mount
Connector Mounting Type	Board Mount
Mating Alignment	With
PCB Mount Alignment	Without
PCB Mount Retention	With
Housing Features	
Housing Material	PA 66
Centerline (Pitch)	5 mm[.197 in]
Dimensions	
Connector Length	32.84 mm[1.293 in]
Connector Height	11.79 mm[.464 in]



Connector Width	18.72 mm[.737 in]
Row-to-Row Spacing	5 mm[.197 in]
Usage Conditions	
Operating Temperature Range	-55 – 130 °C[-67 – 266 °F]
Operation/Application	
Circuit Application	Power & Signal
Industry Standards	
Agency/Standard	CSA, UL, VDE
UL Flammability Rating	UL 94V-0
Packaging Features	
Packaging Quantity	40

Tray

Product Compliance

Packaging Type

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2022 (224) Candidate List Declared Against: JUNE 2022 (224) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach



Compatible Parts



Documents

Product Drawings

METRIMATE PIN HEADER ASSY,18P

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_207444-9_U.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_207444-9_U.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_207444-9_U.3d_stp.zip

English

Customer View Model

ENG_CVM_207444-9_L.3d_igs.zip

English

Customer View Model

ENG_CVM_207444-9_L.3d_stp.zip

English

Customer View Model

ENG_CVM_207444-9_L.2d_dxf.zip

English

3D PDF

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

METRIMATE_PIN_SOCKET_CATALOG

English

PCB Mount Header, Vertical, Wire-to-Board, 18 Position, 5 mm [.197 in] Centerline, Fully Shrouded, Tin, Through Hole - Solder, Power & Signal, Black



Product Specifications

Product Specification

English

Product Environmental Compliance

Product Compliance

English

Product Compliance

English

Agency Approvals

CSA Certificate

English