

#### Alcoswitch

TE Internal #: 2-1437579-7

Slide Switches, Four Pole - Double Throw Configuration (Pole-

Throw), Vertical, Copper, Single Actuator, 2 Position, On None On, .

4 A, 20 VDC

View on TE.com >



Relays, Contactors & Switches > Switches > Slide Switches



Configuration (Pole-Throw): Four Pole - Double Throw

Slide Switch Mounting Angle: Vertical

Contact Base Material: Copper
Number of Actuators: Single

Number of Slide Switch Positions: 2

## **Features**

## **Product Type Features**

Threaded Case	Without
Switch Type	Slide
Product Type	Switch
Terminal Configuration	Standard
Actuator Style	Extended, Side

## **Configuration Features**

Terminals Connected	2-3
Configuration (Pole-Throw)	Four Pole - Double Throw
Number of Actuators	Single
Number of Slide Switch Positions	2
Operating Function	On None On

#### **Electrical Characteristics**

	Slide Switch Voltage Rating (VDC)	20	
--	-----------------------------------	----	--

## **Body Features**

Actuator Material	PBT
Actuator Color	Black

#### **Contact Features**

Contact Base Material	Copper
-----------------------	--------



Slide Switch Contact Current Rating	.4 A
Switch Contact Plating Material	Gold
Termination Features	
Termination Type	PC
Mechanical Attachment	
PCB Mount Retention Type	Extended
Slide Switch Mounting Angle	Vertical
Slide Switch Mounting Type	Through Hole
Dimensions	
PCB Tail Length	3.3 mm[.13 in]
Actuator Length	2.79 mm[.11 in]
Width	9.14 mm[.36 in]
Length	15.8 mm[.62 in]
Identification Marking	
Stamped Marking	With
Industry Standards	
UL Flammability Rating	UL 94V-0

## **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Not Yet Reviewed
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2022 (224) Candidate List Declared Against: JUL 2019 (201) Does not contain REACH SVHC
Halogen Content	Not Yet Reviewed for halogen content
Solder Process Capability	Wave solder capable to 265°C

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these

Slide Switches, Four Pole - Double Throw Configuration (Pole-Throw), Vertical, Copper, Single Actuator, 2 Position, On None On, .4 A, 20 VDC



limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

# Compatible Parts











## **Documents**

Product Drawings
TSS41NGRA=SLIDE R/A TERM 4 POL

English

Datasheets & Catalog Pages
SWITCHES\_CORE\_PROGRAM\_CATALOG

English