# 4DB-P108-03 ✓ ACTIVE

### Buchanan | Buchanan 4DB Series

TE Internal #: 2-1437667-5

Barrier Strips, Dual Barrier, Printed Circuit Pin, Wire-to-Board, 3 Position, 8.26 mm [.325 in] Centerline, 1 Row, 150 V / 300 V,

Buchanan 4DB Series

View on TE.com >



Connectors > Terminal Blocks & Strips > Barrier Strips











Barrier Strip Style: **Dual Barrier** 

Bottom Termination Type: Printed Circuit Pin

Connector System: Wire-to-Board

Number of Positions: 3

Centerline (Pitch): 8.26 mm [ .325 in ]

### **Features**

### **Product Type Features**

Barrier Strip Style

Froduct Type realures	
Product Type	Barrier Strip
Block Style	Flat
Connector System	Wire-to-Board
Connector & Contact Terminates To	Printed Circuit Board
Configuration Features	
Number of Levels	1
Number of Positions	3
Number of Rows	1
Electrical Characteristics	
Current Rating (Max)	10 A, 20 A
Voltage Rating	150 V, 300 V
Body Features	
Color	Black

Dual Barrier



### **Contact Features**

Terminal Material	Copper Alloy
Terminal Plating Finish	Bright
Terminal Plating Material	Tin
Contact Current Rating (Max)	10 A, 20 A

### **Termination Features**

Bottom Termination Type	Printed Circuit Pin	
-------------------------	---------------------	--

### Mechanical Attachment

Mounting Angle	Vertical
Screw Head Type	Wire Clamp Combo Head
Top Termination Type	Wire Clamp Combo Head
Mounting Insert	Without
Screw Plating Material	Zinc Chromate
Screw Material	Steel
Mounting Options	None
Mounting Ears	Without
Screw Size	6-32
Connector Mounting Type	Board Mount

### **Housing Features**

Housing Material	Thermoplastic Polyamide
Centerline (Pitch)	8.26 mm[.325 in]

### **Dimensions**

Length	26.42 mm[1.04 in]
Wire Size	$.3 - 3 \text{ mm}^2$

## **Usage Conditions**

Operating Temperature Range -40 –	105 °C[-40 – 221 °F]
-----------------------------------	----------------------

## Operation/Application

Circuit Application	Power	
Industry Standards		

#### industry Standards

## Packaging Features



Packaging Quantity	70
Packaging Method	Package
Other	
Comment	Do not order screw and captive clamp in combination with other top hardware., Other options available upon request, consult our Product Information Center.

### **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant with Exemptions
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2022 (224) Candidate List Declared Against: JAN 2022 (223) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Wave solder capable to 265°C

### Product Compliance Disclaimer


This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

# **Compatible Parts**





## Also in the Series | Buchanan 4DB Series



### **Documents**

**Product Drawings** 

4DB-P108-03=4DB ASSEMBLY

English

#### **CAD Files**

**Customer View Model** 

ENG\_CVM\_2-1437667-5\_N.3d\_igs.zip

English

3D PDF

English

**Customer View Model** 

ENG\_CVM\_2-1437667-5\_N.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_2-1437667-5\_N.3d\_stp.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_2-1437667-5\_M.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_2-1437667-5\_M.3d\_stp.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_2-1437667-5\_M.2d\_dxf.zip

Barrier Strips, Dual Barrier, Printed Circuit Pin, Wire-to-Board, 3 Position, 8.26 mm [. 325 in] Centerline, 1 Row, 150 V / 300 V, Buchanan 4DB Series



English

3D PDF

3D

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

## Datasheets & Catalog Pages

**BUCHANAN TERMINAL BLOCKS CATALOG - BARRIER STRIPS** 

English

1-1773458-2\_BARRIER\_STRIPS\_QUICK\_REFERENCE\_GUIDE

English

Product Environmental Compliance

MD\_2-1437667-5\_110920172126\_dmtec

English

MD\_2-1437667-5\_110920172126\_dmtec

English