2-1586075-0 ACTIVE

VAL-U-LOK

TE Internal #: 2-1586075-0


Rectangular Connector Housings, Wire-to-Wire, 15 Newton Insertion Force, 20 Position, .165 in [4.2 mm] Centerline, 2 Row,

Nylon, Receptacle, Socket

View on TE.com >



Connectors > Rectangular Connectors > Rectangular Connector Housings



Connector System: Wire-to-Wire

Insertion Force: 15 Newton
Number of Positions: 20

Centerline (Pitch): 4.2 mm [.165 in]
Row-to-Row Spacing: 4.2 mm [.165 in]

Features

Product Type Features

Connector System	Wire-to-Wire
Connector & Housing Type	Receptacle
Sealable	No
Connector & Contact Terminates To	Wire & Cable
Connector Type	Housing
Product Type	Connector
Glow Wire Rating	Standard Part - Not Glow Wire

Configuration Features

Insertion Force	15 Newton
Number of Positions	20
Number of Rows	2

Electrical Characteristics

Operating Voltage	600 VAC	

Contact Features

Mechanical Attachment

Connector Mounting Type	Cable Mount (Free-Hanging)
-------------------------	----------------------------

Housing Features



Centerline (Pitch)	4.2 mm[.165 in]
Housing Material	Nylon
Housing Color	Black
Dimensions	
Row-to-Row Spacing	4.2 mm[.165 in]
Height	11.8 mm[.464 in]
Length	3.2 mm[.125 in]
Width	20 mm[.787 in]
Usage Conditions	
Operating Temperature Range	-40 - 105 °C[-40 - 221 °F]
Operation/Application	
Circuit Application	Power
Industry Standards	
CSA Rating	208567
Agency/Standard	CSA, UL
CSA File Number	208567
UL File Number	E28476
UL Flammability Rating	UL 94V-2

Packaging Features

Packaging Quantity	500
Packaging Method	Bag

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2022 (224) Candidate List Declared Against: JUL 2017 (174) SVHC > Threshold: Not Yet Reviewed



Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per
	homogenous material. Also BFR/CFR/PVC
	Free

Solder Process Capability

Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulations, TE's information on SVHC in articles for this part number is still based on the European Chemical Agency (ECHA) 'Guidance on requirements for substances in articles' (Version: 2, April 2011), applying the 0.1% weight on weight concentration threshold at the finished product level. TE is aware of the European Court of Justice ruling of September 10th, 2015 also known as O5A (Once An Article Always An Article) stating that, in case of 'complex object', the threshold for a SVHC must be applied to both the product as a whole and simultaneously to each of the articles forming part of its composition. TE has evaluated this ruling based on the new ECHA "Guidance on requirements for substances in articles" (June 2017, version 4.0) and will be updating its statements accordingly.

Compatible Parts









TE Part # 2-2029027-0 20P PLUG VAL-U-LOK FH V2 BLK TE Part # 2-2029088-0 20P PLUG VAL-U-LOK V2 PM BLK

TE Part # 2-2029089-0 20P PLUG VAL-U-LOK V2 PM RED TE Part # 2-2029090-0 20P PLUG VAL-U-LOK V2 FH RED Rectangular Connector Housings, Wire-to-Wire, 15 Newton Insertion Force, 20 Position, .165 in [4.2 mm] Centerline, 2 Row, Nylon, Receptacle, Socket



TE Part # 2-2029095-0 20P PLUG VAL-U-LOK V2 PM BLUE

TE Part # 2-2029096-0 20P PLUG VAL-U-LOK V2 FH BLUE

Documents

Product Drawings

20P RCPT VAL-U-LOK V2 BLK

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_2-1586075-0_B.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_2-1586075-0_B.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_2-1586075-0_B.3d_stp.zip

English

By downloading the CAD file I accept and agree to the Terms and Conditions of use.

Product Specifications

Application Specification

English

Agency Approvals

UL Report

English