

CII


TE Internal #: 2-1617806-1

Mid-Range Relays, 2 Form C, DPDT, 2 C/O, Gold Terminal Plating, 12 A, 28 VDC Coil Voltage, 320 Ω Coil Resistance, 115/200Vac (60-400Hz)

View on TE.com >



Relays, Contactors & Switches > Relays > Mil-Aero Relays > Mid-Range Relays



Mid-Range Relay Contact Arrangement: 2 Form C, DPDT, 2 C/O

Coil Suppression Diode: Without

Auxiliary Contacts: Without
Terminal Plating: Gold

Mid-Range Relay Contact Current Rating: 12 A

Mid-Range Relay Contact Arrangement

Auxiliary Contacts

Features

Product Type Features

Enclosure Type

Terminal Configuration	Socket Pins
Product Type	Relay
Relay Type	Military/Aerospace Mid-Range
Electrical Characteristics	
Vibration	30G's, 70 – 3000Hz
Shock	200G's, 6ms
Coil Suppression Diode	Without
Mid-Range Relay Coil Voltage Rating	28 VDC
Mid-Range Relay Coil Resistance	320 Ω
Mid-Range Relay Contact Switching (Max)	115/200Vac (60-400Hz)
Back EMF Suppression	Without
Coil Magnetic System	Polarized, Monostable
Actuating System	DC
Contact Features	

Hermetically Sealed

2 Form C, DPDT, 2 C/O

Without



Terminal Plating	Gold
Mid-Range Relay Contact Current Rating	12 A
Contact Base Material	Silver Cadmium Oxide
Mechanical Attachment	
Mid-Range Relay Mounting Type	Raised Vertical Flange Mount
Usage Conditions	
Operating Temperature Range	-70 – 125 °C

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Not Compliant
EU ELV Directive 2000/53/EC	Not Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2022 (224) Candidate List Declared Against: JAN 2022 (223) SVHC > Threshold: Not Yet Reviewed
Halogen Content	Not Yet Reviewed for halogen content
Solder Process Capability	Not lead free process capable

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulations, TE's information on SVHC in articles for this part number is still based on the European Chemical Agency (ECHA) 'Guidance on requirements for substances in articles' (Version: 2, April 2011), applying the 0.1% weight on weight concentration threshold at the finished product level. TE is aware of the European Court of Justice ruling of September 10th, 2015 also known as O5A (Once An Article Always An Article) stating that, in case of 'complex object', the threshold for a SVHC must be applied to both the product as a whole and simultaneously to each of the articles forming part of its composition. TE has evaluated this ruling based on the new ECHA "Guidance on requirements for substances in articles" (June 2017, version 4.0) and will be updating its statements accordingly.

Compatible Parts





Documents

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_2-1617806-1_A.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_2-1617806-1_A.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_2-1617806-1_A.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages 5-1773450-5_sec5_FCA-212

English