#### **PLASTI-GRIP**

TE Internal #: 2-34150-3

Ring Terminals & Spade Terminals, Ring Tongue, 22 – 16 AWG Wire Size, .26 – 1.65 mm<sup>2</sup> Wire Size, 509 – 3260 CMA Wire Size,

PLASTI-GRIP

View on TE.com >



Terminals & Splices > Ring Terminals & Spade Terminals











Ring & Spade Terminal Type: Ring Tongue

Wire Size: **509 – 3260 CMA** 

Stud Size: 1/4, M6

# **Features**

# **Product Type Features**

Weight per Piece

Ring & Spade Terminal Type

**Contact Features** 

Barrel Type

Shape Description	RING-043
Stud Size	1/4, M6
Sealable	No
Wire Insulation Support Retention Type	Insulation Support
Configuration Features	
Number of Holes	1
Terminal Angle	180°
Electrical Characteristics	
Voltage (Max)	600 V
Body Features	
Inspection Slot	No

.155 g

Closed

Ring Tongue



Terminal Orientation	Straight	
Terminal Plating Material	Tin	
Mechanical Attachment		
Wire Insulation Support	With	
Dimensions		
Wire Size	509 – 3260 CMA	
Stud Diameter	6.73 mm[.265 in]	
Tongue Thickness	.79 mm[.031 in]	
Overall Product Length	27.69 mm[1.09 in]	
Accepts Wire Insulation Diameter (Max)	3.56 mm[.14 in]	
Accepts Wire Insulation Diameter Range	2.67 – 3.56 mm[.105 – .14 in]	
Usage Conditions		
Insulation Option	Partially Insulated	
Operating Temperature Range	105 °C[221 °F]	
Operation/Application		
Compatible With Wire Base Material	Copper	
Compatible With Wire Plating Material	Tin	
Heavy Duty	No	
Industry Standards		
Government Qualified	No	
Packaging Features		
Packaging Quantity	5000	
Packaging Method	Tape Mounted	

# **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2022 (224) Candidate List Declared Against: JAN 2022 (223)



				0 // 10
1)oes	not a	contain	REACH	SVHC

Halogen Content	Not Low Halogen - contains Br or Cl > 900
	ppm.

Solder Process Capability

Not applicable for solder process capability

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

# Compatible Parts












# Also in the Series | PLASTI-GRIP



Compression Connectors(3)



Crimp Wire Pins, Tabs & Ferrules(25)



Ring Terminals & Spade Terminals(537)



Splices(49)



### **Documents**

# **Product Drawings**

PG R 22-16 COMM 22-18 MIL 1/4

English

#### **CAD Files**

**Customer View Model** 

ENG\_CVM\_CVM\_2-34150-3\_S.2d\_dxf.zip

English

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_2-34150-3\_S.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_2-34150-3\_S.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

# **Product Specifications**

**Application Specification** 

English